

LED Cluster

Model	Shape [mm]	Color Component	Quantity of Lamps [EA]	[nm]	Forward Current [IF] [mA]		Luminance Intensity[cd]		Power Dissipation [watt] typ.	Mounting Angle [Degree]	Viewing Angle [Degree]
					typ.	max	min	typ.			
KSL-0820MLOW-S	20	Red	2	660	20	25	0.8	1.2	0.11	6	45
		Green	6	568	40	50	0.8	1.2	0.35		
KSL-1425MLOW-S	25	Red	4	660	20	25	0.7	1	0.21	6	45
		Green	10	568	40	50	1.3	1.8	0.6		
KSL-2230MLOW-S	30	Red	6	660	20	25	2.9	4.2	0.3	6	45
		Green	16	568	80	100	2.2	3.2	0.95		
KSL-2840MLOW-S	40	Red	10	660	20	25	1.5	2	0.5	10	45
		Green	18	568	40	50	1.8	2.8	1.1		
KSL-3340MLOW-S	40	Red	5	660	20	25	2.5	3.5	0.28	10	30
		Green	28	568	80	100	5.5	5	1.45		
KSL-5450MLOW-S	50	Red	7	660	20	25	2.0	4.5	0.51	6	45
		Green	45	568	100	125	4.0	6.0	3.0		
KSL-1030MLF-S	30	Red	5	640	20	25	1.0	1.5	0.24	6	60
		Green	3	568	20	25	3.0	4.0	0.26		
		Blue	2	470	20	25	0.7	1.0	0.17		
KSL-2630MLF-S1A	30	Red	3	660	20	25	1.1	1.5	0.18	6	45
		Green	20	568	80	25	1.8	2.8	0.19		
		Blue	3	470	20	100	0.8	1.1	0.3		



Schareggstrasse 3, CH-5506 Mägenwil
 Tel. +41 62 896 00 48, Fax. +41 62 896 25 80
 info@admatec.ch, www.admatec.ch