

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
1.5	CLAA015CB01AG	CPT	128x128	200cd/m²	200:1					18bit
1.5	LH152J02	LG	128x128			35/15 45/45	27.26x27.26			
1.5	LKC33TMK6YT	NAN	128x128					LED Backlight	T	Tomato TL1771
1.5	LM15TGFNZ26	SHA	128x128	120cd/m²	40:1		26.1x28.15			
1.5	A015AN04	AUO	280x220	170cd/m²	300:1	15/35 45/45	29.96x22.66	LED Backlight	T	
1.5	A015AN01	AUO	280x220	200cd/m²	150:1	10/30 45/45	29.50x22.20	10,000	T	
1.5	A015BL102	AUO	502x240	170cd/m²	300:1	50/50 20/70				
1.7	A017CN01	AUO	480x240	250cd/m²	300:1	45/45 15/35	34.08x25.56	LED Backlight		
1.8	CLAA018DE01AG	CPT	128x160	200cd/m²	300:1					18bit
1.8	LKC34ZMH8YS	NAN	128x160					LED Backlight	T	MagnaChip IS2341
1.8	PT0181216-A601	PALM	128x160				28.03x35.04	LED Backlight		IL19163B
1.8	LMS179FF0	SAM	128x160	240cd/m²	200:1		31.5x42.35			
1.8	CLAA018FE01AG	CPT	176x220	200cd/m²	200:1					18bit
1.8	A018AN03	AUO	280x220	240cd/m²	150:1	10/30 45/45	35.60x26.60		T	
1.8	A018AN03 V1	AUO	280x220	240cd/m²	150:1	40/40 10/30				
1.8	A01AN02 V2	AUO	280x220	50cd/m²	90:1	45/45 10/30				
1.9	LH190Q01	LG	240x320			85/85 85/85	28.8x38.4			
2.0	CLAA020FB01AG	CPT	176x220	200cd/m²	300:1					
2.0	LH200J02	LG	176x220	200cd/m²	350:1	35/15 45/45	31.68x39.60			
2.0	LKC53TML7YT	NAN	176x220					LED Backlight	T	Sam S6D01181C
2.0	PT0201722-A402	PALM	176x220				31.68x39.60	LED Backlight		HX8347-B
2.0	PNG20CW	PALM	176x220	200cd/m²			31.68x39.60	LED Backlight		HX8309A
2.0	LMS200EF0	SAM	176x220				31.68x39.60			
2.0	LQ020QCXX20	SHA	176x220	50cd/m²	400:1		31.68x39.60			
2.0	TFT6987UCDFDW-P-G-F-LED	TRU	176x220	114cd/m²	350:1	35/15 45/45	33.90x42.10	LED Backlight	TR	
2.0	TFT8285UCTDFW-P-G-F-LED	TRU	176x220	220cd/m²	300:1	45/15 45/45	33.90x42.10	LED Backlight	T	
2.0	CLAA020GA01AW	CPT	240x320	200cd/m²	200:1					RGB I/F
2.0	LH200Q04	LG	240x320	250cd/m²	350:1	85/85 85/85	30.6x40.8			
2.0	LH200Q06-A	LG	240x320	250cd/m²	400:1	35/15 45/45	30.6x40.8			
2.0	A020CN01	AUO	480x240	250cd/m²	300:1	35/15 45/45	39.84x29.88	LED Backlight		
2.0	A020BL01	AUO	640x240	200cd/m²	300:1	50/50 20/70	40.64x30.48	LED Backlight		
2.2	LH220J01	LG	176x220	200cd/m²	350:1	15/35 45/45	34.848x43.56			
2.2	OGM-N500	ODT	176x220		250:1	15/35 45/45		LED Backlight		
2.2	LMS220EF0	SAM	176x220	240cd/m²	350:1		34.85x43.56			
2.2	LQ022B8UD05	SHA	176x220	125cd/m²	60:1	30/30 60/60	34.848x43.56	LED Backlight		
2.2	TFT8001UCDFDW-P-G-F-LED	TRU	176x220		300:1	35/15 45/45	39.10x47.86	LED Backlight	TR	
2.2	CLAA022GA01AG	CPT	240x320	200cd/m²	300:1					18bit
2.2	LH220Q12	LG	240x320	400cd/m²	350:1	15/35 45/45	33.84x45.12			
2.2	LH220Q13	LG	240x320	400cd/m²	400:1	85/85 85/85	33.84x45.12			
2.2	LKC35TMK1MT	NAN	240x320					LED Backlight	T	Himax HX8312A
2.2	LKC35TMK1MT	NAN	240x320					LED Backlight	T	Solomon SSD1279

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
2.2	PT0222432-A601	PALM	240x320				33.48x44.64	LED Backlight		HX8347-D
2.2	PMG22AW-TCLW	PALM	240x320	200cd/m²	200:1	35/15 45/45	33.48x44.64	LED Backlight	T	HX8312
2.2	LMS222GC0	SAM	240x320	320cd/m²	500:1		33.84x45.12			
2.2	LMS220GF0	SAM	240x320		500:1		33.48x44.64			
2.2	LTE220QV	SAM	240x320	200cd/m²	400:1					
2.2	LS022Q8UX05	SHA	240x320	300cd/m²	400:1		33.48x44.64			
2.4	CLAA024GG01CW	CPT	160x234	250cd/m²	400:1					8bit RGB
2.4	PD024OX8	PVI	160x234	250cd/m²	350:1	50/50 35/15	48.48x35.76	LED Backlight		
2.4	CLAA024GF11AT	CPT	240x320	200cd/m²	300:1					18bit CPU
2.4	LH240Q31	LG	240x320			35/15 45/45	36.0x48.0			
2.4	LVC46Z806YST	NAN	240x320	200cd/m²			36.72x48.96	LED Backlight	T	
2.4	PT0242432T-A503	PALM	240x320				36.72x48.96	LED Backlight		IL9328 Inkl. Touch
2.4	LMS241GF0	SAM	240x320	290cd/m²	500:1		36.70x48.96			
2.4	LS024Q8XX24	SHA	240x320	250cd/m²	300:1		36.72x48.96			
2.4	MF240320B24-BFW	EBI	320x240				36.72x48.96	LED Backlight	T	IL19320
2.4	OGM-CM2402T-RF050	ODT	320x240	150cd/m²	200:1	35/15 50/50	36.72x48.96	LED Backlight	T	HX8312
2.4	PMG24BW-TCLWU	PALM	320x240	200cd/m²	200:1	15/35 45/45	36.72x48.96	LED Backlight	T	IL19320
2.4	PMG24AW-TCLWU	PALM	320x240	200cd/m²	200:1	35/15 45/45	36.72x48.96	LED Backlight	T	HX8312
2.4	LMS240GC0	SAM	320x240	270cd/m²	300:1		48.72x36.54			
2.4	A024CN02	AUO	480x234	250cd/m²	300:1	45/45 15/35	48.0x35.68	LED Backlight		
2.4	PA025XSC	PVI	480x234	250cd/m²	350:1	50/50 35/15	49.68x37.44	LED Backlight		
2.4	PA025XSB	PVI	480x234	250cd/m²	350:1	50/50 35/15	49.68x37.44	CCFL		
2.5	A025DL02 V4	AUO	320x240	230cd/m²	300:1	20/70 50/50	50.4x37.8	LED Backlight		
2.5	A025DL02 V3	AUO	320x240	230cd/m²	300:1	20/70 50/50	50.4x37.8	LED Backlight		
2.5	A025DL01	AUO	320x240	300cd/m²	200:1	50/50 20/70				
2.5	LH250Q01	LG	320x240		350:1	35/15 45/45	50.88x36.72			
2.5	PFG25BW-TCLW	PALM	320x240	250cd/m²	300:1	40/40 20/50	50.91x38.16	LED Backlight	T	
2.5	LMS250GF0	SAM	320x240	330cd/m²	300:1		50.88x38.16			
2.5	LTV250QV-F01	SAM	320x240	220cd/m²	300:1	80/80 80/65	50.88x38.04	LED Backlight		Wide viewing angle
2.5	LQ025Q3DW02	SHA	320x240	350cd/m²	500:1	80/80 80/80	49.92x37.44	LED Backlight		
2.5	A025CN02	AUO	480x234	250cd/m²	150:1	10/30 45/45	49.20x38.10		T	
2.5	A025BN01	AUO	640x240	250cd/m²	300:1	15/35 45/45	50.56x38.16	LED Backlight		
2.5	A025DL02	AUO	960x240	250cd/m²	300:1	40/60 60/60	50.4x37.8	LED Backlight		
2.6	LMS259HF0	SAM	240x400	280cd/m²	350:1		33.84x56.4			
2.6	LS26B8PX02A	SHA	240x400	220cd/m²	300:1		33.84x56.4			
2.7	NL2432HC17-04B	NEC	240x320	120cd/m²	150:1	35/30 30/30	41.04x54.72	LED Backlight		Inkl. Touch Panel
2.7	NL2432HC17-04A	NEC	240x320	140cd/m²	150:1	35/30 30/30	41.04x54.72	LED Backlight		
2.7	NL2432HC17-05B	NEC	240x320	350cd/m²	400:1	60/30 50/50	41.04x54.72	LED Backlight		Inkl. Touch Panel
2.7	NL2432HC17-07A	NEC	240x320	550cd/m²	400:1	60/30 50/50	41.04x54.72	LED Backlight		
2.7	NL2432HC17-07B	NEC	240x320	500cd/m²	400:1	60/30 50/50	41.04x54.72	LED Backlight		
2.7	NL2432HC17-02B	NEC	240x320	180cd/m²	400:1	60/30 55/55	41.04x54.72	LED Backlight		Inkl. Touch Panel

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
2.7	NL2432HC17-02A	NEC	240x320	200cd/m²	400:1	60/30 50/50	41.04x54.72	LED Backlight		
2.7	A027CW00	AUO	480x234		200:1	15/35 45/45	58.56x33.23			
2.7	A027DN01	AUO	960x240	350cd/m²	300:1	70/70 70/70		LED Backlight		
2.7	A027DL01	AUO	960x240	250cd/m²	300:1	40/60 60/60	57.84x34.20	LED Backlight		
2.8	CLAA028GB01AW	CPT	240x320	200cd/m²	300:1					CPU
2.8	PT0282432T-A802	PALM	240x320				43.2x57.6	LED Backlight		IL9325C inkl. Touch
2.8	LMS283GF07	SAM	240x320	260cd/m²	360:1		43.2x57.6			
2.8	CLAA028JA01AW	CPT	240x400	300cd/m²	450:1					18bit RGB
2.8	LMS283GF0	SAM	240x320	350cd/m²	360:1		43.2x57.6			
2.8	TFT8420DCDFW-P-G-F-LED	TRU	320x240	181cd/m²	100:1	60/40 40/40	47.20x59.85	LED Backlight	TR	
3.0	A030DL02	AUO	320x240	250cd/m²	300:1	40/60 60/60	65.76x36.24	LED Backlight		
3.0	A030DL01	AUO	320x240	350cd/m²	300:1	55/55 60/45	60.0x45.0	LED Backlight		
3.0	LQ030B7DD01	SHA	320x240	110cd/m²	70:1	60/40 60/40	53.76x53.76	LED Backlight		
3.2	PT0322432T-A601	PALM	240x320				48.6x64.8	LED Backlight		HX8347 Inkl. Touch
3.2	LMS320HF0	SAM	240x432	320cd/m²	500:1		39.6x71.28			
3.5	NL2432HC22-41B	NEC	240x320	200cd/m²	150:1	30/35 30/30	53.64x71.52	LED Backlight		Inkl. Touch Panel
3.5	NL2432HC22-40A	NEC	240x320	220cd/m²	150:1	35/35 35/35	53.64x71.52	LED Backlight		
3.5	NL2432HC22-32B	NEC	240x320	100cd/m²	70:1	40/35 40/40	53.64x71.52	LED Backlight		Inkl. Touch Panel
3.5	NL2432HC22-37B	NEC	240x320	350cd/m²	300:1	60/30 55/55	53.64x71.52	LED Backlight		Inkl. Touch Panel
3.5	NL2432HC22-45A	NEC	240x320	100cd/m²	150:1	35/35 35/35	53.64x71.52	LED Backlight	T	
3.5	OGM-TP3501T	ODT	240x320	200cd/m²	100:1	55/55 60/60	53.28x71.04	LED Backlight	TR	
3.5	T-51963GD035J-MLW	OPT	240x320	140cd/m²	90:1	45/45 15/35				
3.5	LTS350Q2-PE2	SAM	240x320	70cd/m²	60:1		53.60x71.50		TR	
3.5	LQ035Q7DH06	SHA	240x320	225cd/m²	80:1	50/50 50/50	53.64x71.52	6xLED		
3.5	LQ035Q7DH07	SHA	240x320	250cd/m²	80:1	50/50 40/40	53.64x71.52	6xLED	TR	
3.5	LQ035Q7DB03F	SHA	240x320	55cd/m²	85:1	50/50 50/50	53.64x71.52	6xLED		
3.5	LQ035Q7DB02	SHA	240x320	50cd/m²	80:1	40/40 40/40	53.64x71.52	LED Backlight		
3.5	LQ035Q7DB02R	SHA	240x320	50cd/m²	70:1	50/50 50/50	53.64x71.52	LED Backlight		
3.5	LQ035Q7DH06	SHA	240x320	225cd/m²			53.64x71.52	6xLED		
3.5	PD035OX1	PVI	320x234	250cd/m²	400:1	50/50 35/15	71.6x52.65	LED Backlight		
3.5	LQ035WC115	CHIL	320x240	250cd/m²	200:1	10/30 40/40	70.08x52.56	LED Backlight		
3.5	CLAA035GC01CT	CPT	320x240	320cd/m²	300:1					24bit parallel RGB
3.5	MF320240B35-BF	EBI	320x240				70.08x52.56	LED Backlight	T	HX8218
3.5	LB350Q02	LG	320x240	300cd/m²	400:	65/65 55/55	70.1x52.6			
3.5	LKC86Z731VT	NAN	320x240					LED Backlight	T	W. viewing/Digital
3.5	LKC86Z731V1T	NAN	320x240					LED Backlight	T	Inkl. Touch Panel
3.5	LVC75Z779VS	NAN	320x240	350cd/m²			70.08x52.56	LED Backlight	T	
3.5	LVC75Z779V1S	NAN	320x240	350cd/m²			70.08x52.56	LED Backlight	T	Inkl. Touch Panel
3.5	OGM-H3501T	ODT	320x240	250cd/m²	300:1	40/60 60/60	70.08x52.56	LED Backlight	T	
3.5	PT0353224-A601	PALM	320x240				70.08x52.56	LED Backlight		HX8238-A
3.5	PT0353224T-A802	PALM	320x240				70.08x52.56	LED Backlight		Inkl. Touch Panel

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
3.5	PMG35BW-TCLW	PALM	320x240	290cd/m²	220:1	45/50 50/50	70.08x52.56	LED Backlight	T	HX8218
3.5	LTV350QV-1	SAM	320x240	250cd/m²	300:1					
3.5	LTV350QV-2	SAM	320x240	320cd/m²	300:1					
3.5	LQ035Q3DW02	SHA	320x240	450cd/m²	500:1	80/80 80/80	70.56x52.92	LED Backlight	T	High Brightness
3.5	TS35ND2501	TOPS	320x240	250cd/m²	300:1	50/55 60/60	70.08x52.56	LED Backlight		
3.5	A035CN01	AUO	480x234	250cd/m²	150:1	10/30 45/45	72.00x50.54		T	
3.5	A035CN02	AUO	480x234	250cd/m²	150:1	45/45 15/35	72.00x50.54	LED Backlight		
3.5	LKC86T724MCKT	NAN	480x234					LED Backlight	T	Analog
3.5	LKC86T724VCKT	NAN	480x234					LED Backlight	T	W. viewing/Analog
3.5	PA035XUJ	PVI	480x234	250cd/m²	350:1	15/35 50/50	71.6x52.65	CCFL		
3.5	PA035XSJ	PVI	480x234	250cd/m²	350:1	15/35 50/50	72.00x50.50	10,000	T	
3.5	NL4864HL11-02A	NEC	480x640	220cd/m²	180:1	30/35 30/30	53.28x71.04	LED Backlight		
3.5	NL4864HL11-01B	NEC	480x640	200cd/m²	180:1	30/35 30/30	53.28x71.04	LED Backlight		Inkl. Touch Panel
3.5	P35EN1	PVI	600x234	360cd/m²	120:1	15/35 55/55	71.70x52.40	10,000	T	
3.5	PD035VX2	PVI	640x480	250cd/m²	350:1	50/50 35/15	72.0x52.56	LED Backlight		
3.5	PD035VX3	PVI	640x480	250cd/m²	400:1	50/50 35/15	72.0x52.56	LED Backlight		
3.5	PD035VL1	PVI	640x480	250cd/m²	350:1	50/50 35/15	72.0x52.56	LED Backlight		
3.5	TD035STEE1	TOPP	640x480	150cd/m²	180:1	80/80 80/80	71.04x53.28	LED 5,000	TR	Inkl. Touch Panel
3.5	PA035XSL	PVI	960x234	250cd/m²	350:1	15/35 50/50	71.6x52.65	LED Backlight		
3.5	PA035XSE	PVI	960x234	250cd/m²	350:1	15/35 50/50	71.60x52.65	10,000	T	
3.6	A036QN01	AUO	320x240	250cd/m²	150:1	30/10 45/45				
3.6	C036QN02	AUO	320x240	350cd/m²	300:1	45/55 60/60	72.96x54.72	LED Backlight		
3.6	OGM-TP3602T	ODT	320x240		300:1	20/50 40/40		LED Backlight		
3.6	LQ036Q1DA01	SHA	320x240	280cd/m²	500:1	80/50 80/80	72.5x54.4	7xLED		
3.6	A036QN02	AUO	320x272	250cd/m²	300:1	40/60 60/60	72.96x54.72	LED Backlight		
3.6	SX09Q005ZZA	HIT	640x480					LED Backlight		
3.6	A036QN02 V0	AUO	960x240	250cd/m²	200:1	60/60 40/60				
3.7	LS037V7DW03	SHA	480x640	200cd/m²	200:1	80/80 80/80	56.16x74.88	9xLED		
3.7	LS037V7DW01	SHA	640x480	165cd/m²	200:1	80/80 80/80	56.16x74.88	9xLED	TR	Inkl. Touch Panel
3.8	LQ038Q7DB03R	SHA	240x320	90cd/m²	75:1	50/50 50/50	57.6x76.8	9xLED		
3.8	LQ38Q3DC01	SHA	320x240	240cd/m²	450:1	70/60 70/70	76.8x57.6	2x7 LED		
3.8	LQ038Q5DR01	SHA	320x240	450cd/m²	100:1	40/65 65/65	78.72x53.64	CCFL		
3.8	320GN09T-C-KE000	ODT	480x272					LED Backlight		MONO
4.0	HT040QV1	HYD	320x240	400cd/m²	500:1	70/70 50/50	80.16x60.12	LED Backlight		TTL
4.0	LB040Q02-TD01/02	LG	320x240	400cd/m²	450:1	65/65 50/65	81.60x61.20	20,000	T	
4.0	LB040Q03	LG	320x240	400cd/m²	450:1	65/65 50/60	81.6x61.2	LED Backlight		Wide Temp.
4.0	LB040Q04	LG	320x240	450cd/m²	400:1	70/70 55/55				
4.0	A040CN01	AUO	480x234	250cd/m²	150:1	10/30 45/45	82.11x61.77	LED Backlight	T	
4.0	A040FL01	AUO	480x272	250cd/m²	500:1	80/80 80/80	87.84x49.776	LED Backlight	T	
4.0	CLAA040JC06CT	CPT	480x272	320cd/m²	300:1					TTL
4.0	HTT40WQ1	HYD	480x272	250cd/m²	300:1	65/65 50/55	87.84x49.776	6xLED		

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
4.0	LTE400WQ	SAM	480x272	250cd/m²	300:1					
4.0	LTM04C380K	TOSH	640x480	200cd/m²	250:1					
4.0	PA040XS1	PVI	960x234	350cd/m²	350:1	50/50 35/15	81.12x61.78	CCFL		
4.1	NL8048HL11-01B	NEC	800x600	350cd/m²	400:1	60/80 80/80	88.80x53.28	LED Backlight		Inkl. Touch Panel
4.3	MF480272A43-BF	EBI	480x272	280cd/m²	250:1		95.04x53.856	LED Backlight	T	
4.3	LB043WQ1	LG	480x272	350cd/m²	350:1	65/65 55/55	95.0x53.9			
4.3	LVC95Z780VS	NAN	480x272	360cd/m²			95.04x53.856	LED Backlight	T	
4.3	LVC95Z780V1S	NAN	480x272	240cd/m²			95.04x53.856	LED Backlight	T	Inkl. Touch Panel
4.3	NL4827HC19-05A	NEC	480x272	600cd/m²	500:1	60/80 80/80	95.04x53.856	LED Backlight		
4.3	NL4827HC19-05B	NEC	480x272	500cd/m²	500:1	60/80 80/80	95.04x53.856	LED Backlight		Inkl. Touch Panel
4.3	NL4827HC19-01B	NEC	480x272	450cd/m²	500:1	70/40 50/50	95.04x53.856	LED Backlight		Inkl. Touch Panel
4.3	OGM-S4301T	ODT	480x272		400:1	80/80 80/80		LED Backlight		
4.3	LTG430WQ	SAM	480x272	165cd/m²	400:1					
4.3	LTE430WQ	SAM	480x272	350cd/m²	400:1					
4.3	LQ043T1DG01	SHA	480x272	500cd/m²	300:1	40/60 60/60	95.04x53.856	9xLED		
4.3	LQ043T3DX02	SHA	480x272	165cd/m²	400:1	80/80 80/80	95.04x53.856	7xLED		
4.3	LQ043T3DX04	SHA	480x272	250cd/m²	450:1	80/80 80/80	95.04x53.856	7xLED		
4.3	LQ043T1DG02	SHA	480x272	600cd/m²	300:1	40/60 60/60	95.04x53.856	9xLED		
4.3	HVT43WV1	HYD	800x480	200cd/m²	400:1	90/90 90/90	93.6x56.16	10xLED		W. viewing angle
4.3	AA043MA01	MIT	800x480	200cd/m²	400:1	65/65 45/65		LED Backlight		Wide Temp.
4.8	CLAA048LA0ACT	CPT	800x480	280cd/m²	400:1			LED Backlight		LVDS
4.9	LQ049B5DG04	SHA	320x96	350cd/m²	250:1		120x96			Automotive
5.0	LQ5AW136R	SHA	320x234	320cd/m²	250:1		102.2x74.8			Automotive
5.0	LQ5AW136	SHA	320x234	320cd/m²	60:1	40/65 65/65	102.2x74.8	CCFL		
5.0	LTS500Q1-GF3	SAM	320x240	400cd/m²	200:1		101.8x76.4		T	
5.0	LQ050Q5DR01	SHA	320x240	380cd/m²	100:1	60/60 50/60	101.28x74.76			
5.0	CLAA050JA01CT	CPT	480x272	320cd/m²	350:1					TTL
5.0	LB050WQ2	LG	480x272	400cd/m²	400:1	65/65 55/55	110.7x62.3			
5.0	P50AN3APOL/ P02	PVI	600x234	240cd/m²	120:1	15/35 55/55	102.6x73.9	10,000	T	
5.0	HV050V01	HYD	640x480		600:1	90/90 90/90	101.76x76.32			
5.0	PD050VX2	PVI	640x480	400cd/m²	400:1	60/60 35/50	101.76x74.88	50,000	T	
5.0	AA050ME01	MIT	800x480	420cd/m²	450:1	65/65 65/45		LED Backlight		
5.0	AA050MC01	MIT	800x480	300cd/m²	600:1	85/85 85/85		LED Backlight		
5.0	LTP500WV	SAM	800x480	190cd/m²	250:1					
5.0	PD050XS1	PVI	960x234	400cd/m²	350:1	50/50 35/15	102.72x74.53			
5.5	NL3224AC35-01	NEC	320x240	250cd/m²	85:1	45/45 30/15				
5.5	NL3224BC35-20	NEC	320x240	400cd/m²	400:1	55/55 50/40				
5.5	NL3224BC35-21	NEC	320x240	400cd/m²	400:1	55/55 50/40				
5.5	NL3224BC35-22	NEC	320x240	750cd/m²	500:1	55/55 50/40				
5.6	A056DN01	AUO	320x234	300cd/m²	250:1	40/60 60/60	113.2x84.7	10,000	T	
5.6	LQ056WA019	CHIL	320x234	350cd/m²	200:1	10/30 40/40	113.28x84.708	15,000		

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
5.6	AT056TN03V1	INNO	320x234	350cd/m²	300:1	45/65 65/65	113.28x84.708	20,000		
5.7	G057QN01 V0	AUO	320x240	400cd/m²	600:1	70/70 60/60	115.2x86.4	LED Backlight		Wide Temp.
5.7	G057QN01	AUO	320x240	400cd/m²	800:1	80/80 70/70	115.2x86.4	LED Backlight		
5.7	LQ057AC111	CHIL	320x240	350cd/m²	200:1	50/55 65/65	115.25x86.4	LED Backlight		
5.7	MF320240B57-BF	EBI	320x240				115.2x86.4	LED Backlight	T	HX8218
5.7	TX14D11VM1CBA	HIT	320x240	350cd/m²	150:1	65/65 50/70				
5.7	TX14D12VM1CBA	HIT	320x240	350cd/m²	350:1	65/65 50/70				
5.7	LM740-0A	NAN	320x240	400cd/m²	250:1	60/70 70/70	115.2x86.4	LED 40,000	T	18bit
5.7	LKCEAZ740YKS	NAN	320x240	400cd/m²	250:1	60/70 70/70	115.2x86.4	LED 40,000	T	18bit
5.7	LM740-0B	NAN	320x240	450cd/m²	250:1	60/70 70/70	115.2x86.4	CCFL 40,000	T	18bit
5.7	LKBEAZ740YKS	NAN	320x240	450cd/m²	250:1	60/70 70/70	115.2x86.4	CCFL 40,000	T	18bit
5.7	LM740-1A	NAN	320x240	320cd/m²	250:1	60/70 70/70	115.2x86.4	LED 40,000	T	Incl. Touch Panel
5.7	LKCEAZ740Y1KS	NAN	320x240	320cd/m²	250:1	60/70 70/70	115.2x86.4	LED 40,000	T	Incl. Touch Panel
5.7	LM740-1	NAN	320x240	330cd/m²	250:1	60/70 70/70	115.2x86.4	CCFL 40,000	T	Incl. Touch Panel
5.7	LKBEAZ740Y3KS	NAN	320x240	330cd/m²	250:1	60/70 70/70	115.2x86.4	CCFL 40,000	T	Incl. Touch Panel
5.7	LKCEAZ740V4KS	NAN	320x240	300cd/m²			115.2x86.4	LED 40,000	T	
5.7	OGM-CM5700T	ODT	320x240	300cd/m²	250:1	15/35 45/45	115.2x86.4	LED Backlight	T	
5.7	PMG57BW-TCLW	PALM	320x240	380cd/m²	250:1	50/45 50/50	115.2x86.4	LED Backlight	T	
5.7	PD057VU4	PVI	320x240	500cd/m²	400:1	65/65 65/40	115.26x86.4	CCFL		
5.7	PD057VU5	PVI	320x240	700cd/m²	400:1	65/65 65/40	115.26x86.4	LED Backlight		
5.7	PD057VU1	PVI	320x240	500cd/m²	400:1	65/65 65/40	115.26x86.4			W. viewing angle
5.7	LQ057Q3DG02	SHA	320x240	320cd/m²	500:1	65/80 80/80	115.2x86.4	LED Backlight		
5.7	LQ057Q3DG01	SHA	320x240	320cd/m²	500:1	65/80 80/80	115.2x86.4	LED Backlight		Incl. Touch Panel
5.7	LQ057Q3DC02	SHA	320x240	350cd/m²	60:1	60/60 60/35	115.2x86.4			
5.7	LQ057Q3DC12	SHA	320x240	500cd/m²	350:1	65/40 65/65	115.2x86.4	50,000	T	
5.7	TS57ND2B	TOPS	320x240	300cd/m²	400:1	60/45 60/60	115.2x86.4	LED Backlight		
5.7	AM-640480GTMQW-00H	AMP	640x480	220cd/m²	300:1	70/70 50/50	116.16x87.12	LED Backlight	T	TTL
5.7	G057VN01	AUO	640x480	400cd/m²	800:1	80/80 70/70	115.2x86.4	LED Backlight		
5.7	G057VN01 V0	AUO	640x480	400cd/m²	600:1	70/70 60/60	115.2x86.4	LED Backlight		Wide Temp.
5.7	CLAA057VA01CT	CPT	640x480	180cd/m²	400:1			LED Backlight		TTL
5.7	CLAA057VA01CW	CPT	640x480	220cd/m²	300:1	70/70 50/50	116.16x87.12	LED Backlight	T	TTL
5.7	CLAA057VGA01	CPT	640x480	220cd/m²	300:1	70/70 50/50	116.16x87.12	LED Backlight	T	TTL
5.7	AA057VF02	MIT	640x480	400cd/m²	600:1	80/80 80/60		LED Backlight		
5.7	AA057VG02	MIT	640x480	250cd/m²	185:1	80/80 80/60		LED Backlight		
5.7	LVCC9Z803YST	NAN	640x480	300cd/m²			115.2x86.4	LED Backlight		
5.7	NL6448BC18-01F	NEC	640x480	800cd/m²	850:1	80/80 80/80	116.16x87.12	LED Backlight		
5.7	NL6448BC18-01	NEC	640x480	400cd/m²	850:1	80/80 80/80	116.16x87.12	LED Backlight		
5.7	PT0576448-A001	PALM	640x480	400cd/m²	300:1	60/55 60/60	115.2x86.4	LED Backlight	T	
5.7	PD057VT2	PVI	640x480	500cd/m²	600:1	80/80 50/70	115.26x86.4	CCFL		
5.7	LQ057V3DG01	SHA	640x480	400cd/m²	600:1	80/80 80/70	115.2x86.4	CCFL 50,000	T	Wide Temp.
6.1	CLAA061LA0ACW	CPT	800x480	500cd/m²	400:1			LED Backlight		TTL

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
6.2	TX16D11VM2CBA	HIT	320x240	350cd/m²	350:1	60/60 50/55				
6.3	NL10276BC12-02	NEC	1024x768	250cd/m²	500:1	60/60 45/60				
6.3	LTM06C310	TOSH	1024x768	150cd/m²	250:1					
6.4	LQ064A5CG01	SHA	480x234	350cd/m²	100:1	60/60 35/60				
6.4	LB064V02-A1	LG	640x480	250cd/m²	300:1	15/35 45/45	130.6x97.9	20,000	T	
6.4	LB064V02	LG	640x480	250cd/m²	400:1	65/65 50/60	130.56x97.92	20,000		
6.4	PD064VT5	PVI	640x480	400cd/m²	400:1	50/50 35/15	129.6x97.4			
6.4	PD064VT4	PVI	640x480	400cd/m²	400:1	60/60 55/40	129.6x97.4			
6.4	PD064VL1	PVI	640x480	400cd/m²	400:1	60/60 55/40	129.6x97.4			
6.4	PD064VX1	PVI	640x480		400:1	50/50 35/15	129.6x97.4			
6.4	PD064VT2	PVI	640x480	150cd/m²	400:1	45/45 35/15	129.6x97.4	20,000	T	
6.4	V16C6448AC	PVI	640x480	300cd/m²	120:1	15/35 55/55	129.6x97.4	20,000	T	
6.4	PD064VT1	PVI	640x480	400cd/m²	400:1	15/35 50/50	129.6x97.4	20,000	T	
6.4	LQ64D341	SHA	640x480	300cd/m²	100:1	40/70 70/70	130.6x97.0	50,000	T	
6.4	LQ64D343	SHA	640x480	300cd/m²	300:1	45/45 60/60	130.6x97.0	50,000	T	
6.4	LQ064V1DS11	SHA	640x480	300cd/m²	150:1	60/60 35/55				
6.4	LQ064V3DG01	SHA	640x480	350cd/m²	350:1	60/60 35/55	130.56x97.92			
6.4	PA064PS1	PVI	960x234	330cd/m²	150:1	40/55 60/60	129.6x97.4	10,000	T	
6.4	PA064DS2	PVI	960x234	330cd/m²	150:1	15/35 50/50	129.6x97.3	10,000	T	
6.5	NL10276BC13-01C	NEC	1024x768	650cd/m²	500:1	80/60 80/80	132.096x99.072			LED Backlight
6.5	NL10276BC13-01	NEC	1024x768	500cd/m²	500:1	80/60 80/80	132.096x99.072	LED Backlight		
6.5	PW065XS1	PVI	1200x234	400cd/m²	350:1	60/60 55/40	143.4x79.32			
6.5	A065GW01	AUO	400x234	500cd/m²	300:1	40/45 60/60	143.4x79.3	40,000	T	W
6.5	C065GW01	AUO	400x234	500cd/m²	300:1	45/60 60/60	143.4x79.326	CCFL		
6.5	LB065W01(W/T-CON)	LG	400x234	450cd/m²	400:1	55/65 65/65	144.0x79.3	20,000	T	W
6.5	LB065WQ2	LG	400x234	500cd/m²	400:1	60/60 45/45	143.4x79.3			
6.5	LQ065T5AR06	SHA	400x234	420cd/m²	250:1		143.4x79.326			Automotive
6.5	LVM104XSB-01	VER	400x234	450cd/m²		65/65 50/65	143.4x79.3		T	
6.5	LB065WQ4	LG	400x240	450cd/m²	400:1	70/70 55/55	143.4x79.3			
6.5	LB065WQ3	LG	400x240	450cd/m²	400:1	65/65 50/65	134.4x79.32	20,000		Wide Temp.
6.5	LQ065T9DR53U	SHA	400x240	180cd/m²	60:1		143.4x79.326			Automotive
6.5	LQ065T9DR51	SHA	400x240	220cd/m²	60:1	50/50 50/50	143.4x79.326	10,000	T	
6.5	LQ065T9DZ03	SHA	400x240	250cd/m²			143.4x79.326			
6.5	G065VN01 V0	AUO	640x480	500cd/m²	600:1	70/70 60/60	132.48x99.36	2xCCFL		Wide Temp.
6.5	G065VN01 V1	AUO	640x480	500cd/m²	600:1	70/70 60/60	132.48x99.36	2xCCFL		Wide Temp.
6.5	G065VN01	AUO	640x480	500cd/m²	500:1	70/70 60/60				Wide Temp.
6.5	AA065VB05	MIT	640x480	400cd/m²	600:1	80/80 80/60		2xCCFL		
6.5	AA065VB08	MIT	640x480	600cd/m²	750:1	80/80 80/60		2xCCFL		
6.5	AA065VD01	MIT	640x480	700cd/m²	600:1	80/80 80/60		LED Backlight		
6.5	AA065VB01	MIT	640x480	400cd/m²	600:1	50/60 70/70	132.48x99.36	50,000		Wide Temp.
6.5	NL6448BC20-20	NEC	640x480	650cd/m²	600:1	80/60 80/80	132.48x99.36			LED Backlight

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
6.5	NL6448BC20-21D	NEC	640x480	550cd/m²	600:1	80/60 80/80	132.48x99.36			LED Backlight
6.5	NL6448BC20-21C	NEC	640x480	800cd/m²	600:1	80/60 80/80	132.48x99.36			LED Backlight
6.5	NL6448BC20-08E	NEC	640x480	300cd/m²	250:1	50/50 50/50				
6.5	NL10276BC20-18D	NEC	640x480	400cd/m²	600:1	80/80 80/80				
6.5	NL6448BC20-14	NEC	640x480	500cd/m²	400:1	50/50 35/45				
6.5	T-51750GD065J-FW-AB	OPT	640x480	400cd/m²	300:1	55/55 30/60				
6.5	T-51750GD065J-FW-A-AA	OPT	640x480	400cd/m²	300:1	55/55 30/60				
6.5	LTA065A041F	TOSH	640x480	400cd/m²	250:1	60/60 60/30				
6.5	LTA065A043F	TOSH	640x480	400cd/m²	250:1	60/60 60/30				
6.5	C065VL01	AUO	800x480	550cd/m²	300:1	40/60 55/55	143.4x79.2	LED Backlight		
6.8	A068EN01-1	AUO	1152x234	300cd/m²	150:1	30/60 60/60	138.2x103.4	10,000	T	
7.0	CLAA070NA01CT	CPT	1024x600	250cd/m²	400:1					LVDS
7.0	CLAA070NC0BCT	CPT	1024x600	300cd/m²	400:1					LVDS
7.0	CLAA070NC0DCT	CPT	1024x600	300cd/m²	400:1			LED Backlight		LVDS
7.0	PW070XS1	PVI	1440x234	400cd/m²	350:1	60/60 50/40	154.1x87.1	40,000	T	
7.0	LB070WQ3	LG	400x234	400cd/m²	400:1	70/70 55/55	156.0x82.7			
7.0	A070FW03	AUO	480x234	400cd/m²	300:1	40/65 65/65	154.08x86.58	CCFL	T	
7.0	A070FW03-1	AUO	480x234	500cd/m²	300:1	40/60 60/60	154.08x86.58	10,000	T	W
7.0	C070FW01	AUO	480x234	500cd/m²	300:1	40/60 60/60	154.08x86.58	CCFL		
7.0	LR070WA016V4	CHIL	480x234	350cd/m²	350:1	40/60 60/60	154.08x86.58	15,000		
7.0	CLAA070JA05CW	CPT	480x234	350cd/m²	400:1					Analog
7.0	CLAA069JA11CW	CPT	480x234	500cd/m²	400:1			LED Backlight		Analog
7.0	CLAA070JA0BCW	CPT	480x234	450cd/m²	400:1			LED Backlight		Analog
7.0	AT070TN01V1	INNO	480x234	350cd/m²	300:1	40/60 60/60	154.08x86.58	10,000		
7.0	LB070W02-C5K1	LG	480x234	400cd/m²	400:1	50/65 65/56	154.1x86.6	20,000	T	W
7.0	LB070WQ4	LG	480x234	450cd/m²	400:1	70/70 55/55	156.25x82.37			
7.0	LB070W02	LG	480x234	400cd/m²	400:1	65/65 55/55	154.08x86.58			
7.0	LKBGAZV29YCKT	NAN	480x234						T	W. viewing/Analog
7.0	NL4823BC37-05	NEC	480x234	400cd/m²	600:1	60/80 80/80	154.08x87.048			
7.0	NL4823HC37-03	NEC	480x234	450cd/m²	300:1	85/85 85/85				
7.0	T-51383L070J-FW-P-AA	OPT	480x234	400cd/m²	150:1	55/55 15/30				
7.0	LTS700W1-CF2(W/O T-CON)	SAM	480x234	450cd/m²	150:1		154.1x86.6		T	
7.0	LTE700WQ	SAM	480x234	450cd/m²	500:1					
7.0	TS70WA0115V.2	TOPS	480x234	450cd/m²	550:1	55/60 75/75	154.08x86.58	25,000		
7.0	LVM070W03	VER	480x234	400cd/m²		65/65 65/50	154.1x86.6		T	
7.0	LQ70T5DR01	SHA	480x240	400cd/m²	250:1		154.1x87			
7.0	TX18D17VM2BAA	HIT	480x290	350cd/m²	350:1	60/60 60/40				
7.0	JLPA070VW01-2	AUO	800x480	320cd/m²	300:1	50/70 70/70	152.4x91.44			inkl. Touch Panel
7.0	A070VW02	AUO	800x480	220cd/m²	300:1	40/60 60/60	152.4x91.44	LED Backlight		
7.0	G070VW01 V0	AUO	800x480	400cd/m²	500:1	80/80 80/80	152.4x91.44	LED Backlight		
7.0	A070VW01	AUO	800x480	400cd/m²	300:1	40/60 60/60	152.4x91.4		T	W

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
7.0	C070VW02	AUO	800x480	400cd/m²	300:1	40/60 60/60	152.4x91.44	LED Backlight		
7.0	G070Y1	CMO	800x480	450cd/m²	500:1	60/60 70/70	152.4x91.4			Wide Temp.
7.0	CLAA069LA0ACW	CPT	800x480	500cd/m²	400:1			LED Backlight		TTL
7.0	CLAA070LD0ACW	CPT	800x480	200cd/m²	400:1			LED Backlight		TTL
7.0	CLAA070LD0DCW	CPT	800x480	500cd/m²	400:1			LED Backlight		TTL
7.0	CLAA070LC01CW	CPT	800x480	220cd/m²	400:1					TTL
7.0	CLAA070LC0ACW	CPT	800x480	220cd/m²	400:1					TTL
7.0	CLAA070LC0BCW	CPT	800x480	220cd/m²	400:1					LVDS
7.0	TX18D16VM1CAA	HIT	800x480	350cd/m²	350:1	60/60 60/40				
7.0	LB070WV3	LG	800x480	600cd/m²	700:1	89/89 89/89	152.4x91.44			
7.0	LB070WV1	LG	800x480	400cd/m²	400:1	70/70 55/55	152.4x91.44			
7.0	NL8048BC19-02	NEC	800x480	400cd/m²	1000:1	80/80 80/80	152.4x91.44	LED Backlight		
7.0	NL8048BC19-02C	NEC	800x480	550cd/m²	800:	80/80 80/80	152.4x91.44	LED Backlight		
7.0	NL8048BC19-11D	NEC	800x480	400cd/m²	600:1	88/88 88/88	152.4x91.44	LED Backlight		
7.0	PM070WX1	PVI	800x480	400cd/m²	400:1	50/50 35/40	154.08x87.05	CCFL		
7.0	PM070WX2	PVI	800x480				152.4x91.44	CCFL		inkl. Touch Panel
7.0	LTP700WV-F01	SAM	800x480	350cd/m²	300:1	65/65 55/60	163.2x104.0	LED Backlight		
7.0	LTC700WV	SAM	800x480	450cd/m²	250:1					
7.0	LMS700KF01-001	SAM	800x480	280cd/m²	300:1	65/65 50/60	152.4x91.44	LED Backlight		
7.0	LMS700KF06	SAM	800x480	350cd/m²	400:1	55/55 65/65	152.4x91.44	LED Backlight		
7.0	LMS700KF15	SAM	800x480	350cd/m²	700:1	70/70 70/70	152.4x91.44	LED Backlight		
7.0	LMS700KF01	SAM	800x480	280cd/m²	300:1	65/65 50/60	152.4x91.44	LED Backlight		
7.0	LQ70Y5DR04	SHA	800x480	400cd/m²	250:1		152.4x91.44			
7.0	LQ070Y5DG02	SHA	800x480	380cd/m²	100:1	60/60 40/60				
7.0	CLAA070MA0ACW	CPT	800x600	250cd/m²	500:1			LED Backlight		TTL
7.0	LTS700W1-CF1(W/O T-CON)	SAM							T	
7.5	LQ075V3DG01	SHA	640x480	400cd/m²	600:1		151.68x113.76			
7.7	LTM07C388	TOSH	640x960	200cd/m²	250:1					
7.9	PA079DS4	PVI		350cd/m²	350:1	40/55 60/60	161.3x117.9	25,000	T	
8.0	PA080XS1	PVI	1440x468	400cd/m²	350:1	55/55 35/15	161.28x117.94	30,000		
8.0	CLAA080JA11CW	CPT	480x220	200cd/m²	400:1			LED Backlight		Analog
8.0	FG080010DNCWAG04	DATA	640x480	400cd/m²	250:1	65/65 55/65	162.2x121.7	50,000	T	
8.0	LQ080V3DG01	SHA	640x480	380cd/m²	250:1	60/60 50/60				
8.0	LQ080V3DG01S	SHA	640x480	380cd/m²	250:1	60/60 50/60				
8.0	C080VW02	AUO	800x480	400cd/m²	300:1	40/60 60/60	175.20x105.12	LED Backlight		
8.0	CLAA080LA0ACW	CPT	800x480	200cd/m²	500:1			LED Backlight		TTL
8.0	TX20D16VM2BAA	HIT	800x480	350cd/m²	350:1	60/60 60/40				
8.0	HX080WV1	HYD	800x480	600cd/m²	700:1	90/90 90/90	174.0x104.4	LED Backlight		TTL
8.0	LB080WV3-B1	LG	800x480	400cd/m²	400:1	60/60 40/50	176.64x99.36	20,000	T	
8.0	LB080WV3-B2	LG	800x480	400cd/m²	400:1	60/60 40/50	176.64x99.36	20,000	T	
8.0	LB080WV3	LG	800x480	400cd/m²	400:1	60/60 45/45				

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
8.0	LB080WV4	LG	800x480	500cd/m²	400:1	70/70 60/50	176.64x99.36	20,000		
8.0	LQ080Y5DR02	SHA	800x480	625cd/m²	250:1	60/60 50/50	174x104.4			
8.0	CLAA080MB0DCW	CPT	800x600	250cd/m²	500:1			LED Backlight		TTL
8.0	CLAA080MA01CW	CPT	800x600	250cd/m²	500:1					TTL
8.0	AT080TN42	INNO	800x600	250cd/m²	500:1	70/70 50/70	162x121.5	20,000	T	W. viewing angle
8.4	AA084XA03	MIT	1024x768	300cd/m²	400:1	60/50 65/65		50,000		Wide Temp.
8.4	NL10276BC16-01	NEC	1024x768	400cd/m²	400:1	85/85 85/85				
8.4	T-51639D084U-FW-A-AA	OPT	1024x768	300cd/m²	350:1	60/60 50/40				
8.4	T-51639D084JU-FW-A-AB	OPT	1024x768	300cd/m²	400:1	65/65 60/50				
8.4	PW084XS1	PVI	1440x234	400cd/m²	350:1	40/50 60/60	185.8x104.6		T	
8.4	LR084WA011V.0	CHIL	480x234	300cd/m²	350:1	15/30 40/40	185.76x104.6	15,000		
8.4	AA084VG01	MIT	640x480	800cd/m²	600:1	80/80 80/60		LED Backlight		High Brightness
8.4	AA084VF03	MIT	640x480	480cd/m²	600:1	80/80 80/60		50,000		
8.4	AA084VC04	MIT	640x480	480cd/m²	500:1	50/60 65/65	170.9x128.2	50,000		Wide Temp.
8.4	AA084VF01	MIT	640x480	480cd/m²	600:1	80/80 80/60		50,000		
8.4	AA084VE01	MIT	640x480	200cd/m²	200:1	80/80 50/70	170.9x128.2	50,000		Wide Temp.
8.4	AA084VC05	MIT	640x480	480cd/m²	500:1	50/60 65/65	170.9x128.2	50,000		Wide Temp.
8.4	AA084VC02	MIT	640x480	450cd/m²	450:1	50/60 65/65	170.9x128.2	50,000	T	
8.4	NL6448BC26-15	NEC	640x480	450cd/m²	600:1	80/60 80/80	170.88x128.16	CCFL		
8.4	NL6448BC26-26	NEC	640x480	450cd/m²	600:1	80/60 80/80	170.88x128.16	LED Backlight		
8.4	NL6448BC26-09C	NEC	640x480	750cd/m²	600:1	80/60 80/80	170.88x128.16	50,000		
8.4	NL6448BC26-09	NEC	640x480	450cd/m²	600:1	80/60 80/80	170.88x128.16	50,000		
8.4	NL6448BC26-08D	NEC	640x480	400cd/m²	800:1	85/85 85/85				
8.4	NL6448BC26-01	NEC	640x480	450cd/m²	500:1	55/55 40/70				
8.4	NL6448BC26-03	NEC	640x480	450cd/m²	500:1	70/40 55/55				
8.4	T-51638D084-FW-A-AA	OPT	640x480	450cd/m²	450:1	65/65 50/60				
8.4	T-51638D084J-FW-A-AC	OPT	640x480	480cd/m²	500:1	65/65 50/60				
8.4	T-51638D084J-FW-A-AA	OPT	640x480	480cd/m²	500:1	65/65 50/60				
8.4	LQ084V1DG41	SHA	640x480	400cd/m²	900:1	60/50 70/70	170.9x128.2	1xCCFL	T	
8.4	LQ084VDG11	SHA	640x480	300cd/m²	250:1		170.9x129.6	50,000	T	
8.4	LQ084V1DG21	SHA	640x480	300cd/m²	300:1	55/55 40/55	170.9x129.6			
8.4	LQ084V3DG01	SHA	640x480	400cd/m²	600:1		170.9x129.6			
8.4	B084SN02	AUO	800x600	150cd/m²	350:1	40/40 60/60	170.4x127.8	20,000	T	
8.4	G084SN03 V2	AUO	800x600	180cd/m²	500:1	65/65 65/45				
8.4	B084SN03	AUO	800x600	200cd/m²	350:1	60/40 60/60	170.4x127.8	20,000	T	
8.4	G084SN02	AUO	800x600	200cd/m²	500:1	50/65 65/65	170.4x127.8			
8.4	G084SN03	AUO	800x600	220cd/m²	500:1	55/55 65/65				
8.4	G084SN03 V0	AUO	800x600	220cd/m²	500:1	65/65 65/45				
8.4	G084SN03 V1	AUO	800x600	250cd/m²	600:1	80/80 70/70	170x4.127.8	1xCCFL		
8.4	G084SN05 V1	AUO	800x600	280cd/m²	350:1	60/60 60/40				
8.4	G084SN05 V7	AUO	800x600	450cd/m²	600:1	80/80 70/70	170.4x127.8	2xCCFL		

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
8.4	G084SN05 V8	AUO	800x600	450cd/m²	600:1	80/80 70/70	170.4x127.8	LED Backlight		
8.4	G084SN05	AUO	800x600	350cd/m²	350:1	60/40 60/60	170.4x127.8	50,000	T	
8.4	G084SN05 V1	AUO	800x600	350cd/m²	350:1	60/40 60/60	170.4x127.8	50,000	T	
8.4	G084SN05 V2	AUO	800x600	350cd/m²	350:1	60/40 60/60	170.4x127.8	50,000	T	
8.4	G084SN05	AUO	800x600	450cd/m²	500:1	55/55 45/55				
8.4	LB084S01	LG	800x600	600cd/m²	600:1	75/75 60/60	170.4x127.8			
8.4	AA084SA01	MIT	800x600	400cd/m²	600:1	80/80 80/60		2xCCFL		
8.4	AA084SB01	MIT	800x600	600cd/m²	600:1	80/80 80/60		LED Backlight		
8.4	NL8060BC21-03	NEC	800x600	650cd/m²	600:1	80/60 80/80	170.4x127.8			
8.4	NL8060BC21-02	NEC	800x600	400cd/m²	600:1	80/60 80/80	170.4x127.8			
8.4	NL8060BC21-04	NEC	800x600	400cd/m²	600:1	80/60 80/80	170.4x127.8			
8.4	NL8060BC21-06	NEC	800x600	650cd/m²	600:1	80/60 80/80	170.4x127.8	CCFL		
8.4	LQ084S3DG01	SHA	800x600	350cd/m²	250:1	60/60 40/60	170.4x127.8			
8.4	LQ084S3DG01R	SHA	800x600	350cd/m²	250:1	60/60 40/60				
8.4	LQ084S3LG01	SHA	800x600	400cd/m²	600:1		170.4x127.8			
8.4	LTM08C321	TOSH	800x600	350cd/m²	250:1		170.4x127.8	50,000	T	
8.4	LTM08C343S	TOSH	800x600	130cd/m²	250:1					
8.4	LTM08C351	TOSH	800x600	350cd/m²	250:1		170.4x127.8	50,000		W. viewing angle
8.4	LTM08C351S	TOSH	800x600	350cd/m²	300:1	50/50 30/60				
8.4	LTM084P363	TOSH	800x600	350cd/m²	300:1					
8.4	LTM08C351L	TOSH	800x600	350cd/m²	300:1	50/50 30/60				
8.5	A085FW01	AUO	480x234	400cd/m²	300:1	65/65 50/65	187.20x105.30	CCFL		
8.8	LQ088H9DZ03	SHA	640x240	250cd/m²			209.28x78.48			
8.9	CLAA089NA0FCW	CPT	1024x600	220cd/m²	400:1			LED Backlight		LVDS
8.9	NL10260BC19-01D	NEC	1024x600	300cd/m²	700:1	88/88 88/88	195.072x113.4	LED Backlight		
8.9	HV089WX1	HYD	1280x768	300cd/m²	500:1	90/90 90/90	193.92x116.35	LED Backlight		
9.0	PW090XS2	PVI	1920x220	400cd/m²	350:1	60/60 50/40	202.56x105.27			
9.0	CLAA090JC1ACW	CPT	640x220	200cd/m²	350:1			LED Backlight		Analog
9.0	CLAA090JB01CW	CPT	640x220	200cd/m²	350:1					Analog
9.0	CLAA090LC13CW	CPT	800x480	250cd/m²	400:1			LED Backlight		TTL
9.0	CLAA090LB01CW	CPT	800x480	250cd/m²	400:1					TTL
9.0	TX23D16VM2BAA	HIT	800x480	450cd/m²	350:1	60/60 70/60				
9.0	AA090MD01	MIT	800x480	800cd/m²	600:1	80/80 80/60		50,000		Wide Temp.
9.0	AA090ME01	MIT	800x480	400cd/m²	900:1	85/85 85/85		50,000		Wide Temp.
9.0	AA090MF01	MIT	800x480	800cd/m²	700:1	80/80 80/60		LED Backlight		Wide Temp.
9.0	AA090MC01-G1	MIT	800x480	600cd/m²	600:1	80/80 80/60		50,000		Wide Temp.
9.0	AA090MC01	MIT	800x480	600cd/m²	600:1	80/80 80/60		50,000		Wide Temp.
9.0	NL8048BC24-04	NEC	800x480	350cd/m²	800:1	88/88 88/88	196.8x118.08	CCFL		
9.0	NL8048BC24-09D	NEC	800x480	400cd/m²	600:1	88/88 88/88	196.8x118.08	LED Backlight		
9.0	NL8048BC24-01	NEC	800x480	400cd/m²	500:1	80/80 80/60				
9.6	HSD096MS11-A	HAN	800x600	350cd/m²	450:1	65/65 65/50				

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
10.0	LTA100W1-T02	SAM	800x480	350cd/m²	300:1	45/45 60/60	217.2x130.3	10,000	T	W
10.1	LP101WS1	LG	1024x576	200cd/m²	400:1	25/25 45/45	222.72x125.28			
10.1	B101AW03	AUO	1024x600	200cd/m²	400:1	45/45 25/25	222.7x125.3	LED Backlight		
10.1	B101AW02	AUO	1024x600	200cd/m²	400:1	45/45 25/25	222.7x125.3	LED Backlight		
10.1	CLAA101NB01	CPT	1024x600	200cd/m²	500:1					LVDS
10.1	CLAA101NB03	CPT	1024x600	200cd/m²	500:1					LVDS
10.1	CLAA101NT01	CPT	1024x600	200cd/m²	500:1					LVDS
10.1	LP101WSA	LG	1024x600	200cd/m²	400:1	45/45 15/35	222.72x125.28			
10.1	CLAA101WA01	CPT	1366x768	220cd/m²	600:1					LVDS
10.2	CLAA102NA01CW	CPT	1024x600	400cd/m²	400:1					LVDS
10.2	CLAA102NA0BCW	CPT	1024x600	220cd/m²	400:1			LED Backlight		LVDS
10.2	CLAA102NA32CW	CPT	1024x600	300cd/m²	400:1			CCFL		LVDS
10.2	A102VW01	AUO	800x480	400cd/m²	400:1	50/65 65/65	222.0x133.2			
10.2	LW102WC015V01	CHIL	800x480	400cd/m²	300:1	45/60 60/60	222x132.48	30,000		
10.2	AT102TN01V.1	INNO	800x480	350cd/m²	300:1	45/65 65/65	222x132.48	20,000		
10.2	PM102WX1	PVI	800x480	350cd/m²	400:1	60/60 55/45	22.0x132.48			
10.2	TSAWD0105V3	TOPS	800x480	350cd/m²	300:1	45/60 60/60	222x132.48	30,000		
10.4	G104X1	CMO	1024x768	400cd/m²	1200:1	88/88 88/88	210.4x157.8			Wide viewing angle
10.4	CLAA104XA01CW	CPT	1024x768	300cd/m²	500:1			CCFL		LVDS
10.4	HX104X01	HYD	1024x768	260cd/m²	700:1	90/90 90/90	210.43x157.82	1xCCFL		
10.4	HT10X21-100	HYD	1024x768	150cd/m²	450:1	80/80 80/80	210.4x157.8	10,000	T	
10.4	HT10X21-311	HYD	1024x768	170cd/m²	500:1	80/80 80/80				
10.4	HT10X21-200	HYD	1024x768	180cd/m²			210.4x157.8		T	
10.4	HT10X21	HYD	1024x768	190cd/m²	400:1	90/90 90/90	210.4x157.8	1xCCFL		
10.4	HT104X01	HYD	1024x768	350cd/m²	500:1	89/89 89/89				
10.4	AA104XD12	MIT	1024x768	1000cd/m²	700:1	80/80 65/65		LED Backlight		
10.4	AA104XD02	MIT	1024x768	600cd/m²	700:1	80/80 68/68		LED Backlight		
10.4	AA104XA02	MIT	1024x768	400cd/m²	600:1	80/80 65/65		50,000		Wide Temp.
10.4	NL10276BC20-12	NEC	1024x768	150cd/m²	350:1	40/20 45/45	210.432x157.824	LED Backlight		
10.4	NL10276BC20-18	NEC	1024x768	400cd/m²	1000:1	80/80 80/80	210.432x157.824	LED Backlight		
10.4	NL10276BC20-04	NEC	1024x768	300cd/m²	300:1	60/60 45/60				
10.4	LTM10C313U	TOSH	1024x768	150cd/m²	250:1	55/55 40/35				
10.4	LVM104XSB-01	VER	1024x768	1200cd/m²		80/80 80/80	210.4x157.8		T	
10.4	HV104X01	HYD	1024x768	350cd/m²	500:1	89/89 89/89				
10.4	G104VN01 V1	AUO	640x480	450cd/m²	700:1	80/80 70/70	211.2x158.4	LED Backlight		
10.4	G104VN01	AUO	640x480	450cd/m²	700:1	70/70 60/60	211.2x158.4	2xCCFL		
10.4	G104V1-T01	CMO	640x480	450cd/m²	1500:1	88/88 88/88	211.2x158.4	50,000	T	W.Temp/High Contr.
10.4	G104V1	CMO	640x480	450cd/m²	1500:1	85/85 85/85	211.2x158.4			W.Temp/S.Slim
10.4	TX26D02VM1CAA	HIT	640x480	350cd/m²	500:1	60/60 45/55				
10.4	LB104V03-A1	LG	640x480	400cd/m²	300:1	40/50 60/60	211.2x158.4	40,000	T	
10.4	LB104V03	LG	640x480	400cd/m²	300:1	60/60 45/45	211.2x158.4			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
10.4	AA104VC02	MIT	640x480	430cd/m²	500:1	45/65 65/65				Wide Temp.
10.4	AA104VH12	MIT	640x480	1500cd/m²	700:1	70/70 65/65		LED Backlight		High Brightness
10.4	AA104VH02	MIT	640x480	800cd/m²	700:1	70/70 65/65		LED Backlight		
10.4	AA104VD02	MIT	640x480	500cd/m²	600:1	70/70 65/65		2xCCFL		
10.4	AA104VC01	MIT	640x480	380cd/m²	300:1	45/55 60/60	211.2x158.4	50,000	T	
10.4	AA104VC08	MIT	640x480	430cd/m²	600:1	60/60 65/45		50,000		Wide Temp.
10.4	AA104VC09	MIT	640x480	430cd/m²	500:1	65/65 65/45		50,000		Wide Temp.
10.4	AA104VC10	MIT	640x480	430cd/m²	500:1	65/65 65/45		50,000		Wide Temp.
10.4	AA104VC11	MIT	640x480	380cd/m²	400:1	80/80 70/80		50,000		Wide Temp.
10.4	AA104VF01	MIT	640x480	1000cd/m²	700:1	70/70 65/65		50,000		Wide Temp.,High B.
10.4	NL6448BC33-71D	NEC	640x480	450cd/m²	600:1	80/60 80/80	211.2x158.4	LED Backlight		
10.4	NL6448BC33-74	NEC	640x480	450cd/m²	800:1	88/88 88/88	211.2x158.4	CCFL		
10.4	NL6448BC33-63C	NEC	640x480	450cd/m²	600:1	80/60 80/80	211.2x158.4	50,000		
10.4	NL6448BC33-63D	NEC	640x480	450cd/m²	600:1	80/60 80/80	211.2x158.4	50,000		
10.4	NL6448BC33-64C	NEC	640x480	450cd/m²	600:1	80/60 80/80	211.2x158.4	50,000		
10.4	NL6448BC33-64	NEC	640x480	450cd/m²	600:1	80/60 80/80	211.2x158.4	50,000		
10.4	NL6448BC33-54	NEC	640x480	220cd/m²	350:1	45/45 30/20				
10.4	NL6448AC33-29	NEC	640x480	250cd/m²	150:1	80/80 80/80	211.2x158.4		T	
10.4	NL6448BC33-50	NEC	640x480	250cd/m²	100:1	75/55 40/55				
10.4	NL6448AC33-46	NEC	640x480	350cd/m²	300:1	70/60 70/70	211.2x158.4		T	
10.4	NL6448BC33-31D	NEC	640x480	350cd/m²	300:1	50/50 50/50				
10.4	NL6448BC33-46	NEC	640x480	350cd/m²	300:1	70/70 60/60				
10.4	NL6448BC33-53	NEC	640x480	380cd/m²	500:1	85/85 85/85				
10.4	NL6448BC33-59	NEC	640x480	450cd/m²	600:1	70/70 45/55				
10.4	NL6448CC33-30W	NEC	640x480		150:1	55/55 30/50				
10.4	NL6448CC33-30	NEC	640x480		150:1	55/55 30/50				
10.4	OGM-CM10400T	ODT	640x480		1000:1	88/88 88/88				
10.4	T-51513D104U-FW-A-AB	OPT	640x480	380cd/m²	300:1	60/60 55/45				
10.4	T-51513D104JU-FW-A-AB	OPT	640x480	380cd/m²	300:1	60/60 55/45				
10.4	T-51513D104JU-FW-A-AC	OPT	640x480	380cd/m²	300:1	60/60 55/45	211.2x158.4	50,000		
10.4	T-51513D104J-FW-A-AD	OPT	640x480	430cd/m²	500:1	65/65 45/65				
10.4	PD104VT1	PVI	640x480	330cd/m²	400:1	45/45 40/15	211.2x158.4		T	
10.4	LQ10D368	SHA	640x480	200cd/m²	300:1	60/60 35/55	211.2x158.4			
10.4	LQ104V1DC31	SHA	640x480	250cd/m²	300:1	60/60 35/55	211.2x158.4			
10.4	LQ10D421	SHA	640x480	300cd/m²	100:1	70/70 40/70	211.2x158.4			
10.4	LQ104V1DG11	SHA	640x480	350cd/m²	300:1	40/70 70/70	211.2x158.4	50,000	T	
10.4	LQ104V1DG51	SHA	640x480	350cd/m²	300:1	40/70 70/70	211.2x158.4	50,000	T	
10.4	LQ104V1DG52	SHA	640x480	350cd/m²	300:1	40/70 70/70	211.2x158.4	50,000	T	
10.4	LQ104V1DG61	SHA	640x480	450cd/m²	600:1	50/60 70/70	211.2x158.4			
10.4	LQ104V1DG21	SHA	640x480	350cd/m²	300:1	70/70 40/70	211.2x158.4			
10.4	LQ104V1LG61	SHA	640x480	500cd/m²	450:1	50 60 70/70	211.2x158.4			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
10.4	LQ104V1DG64	SHA	640x480	450cd/m²	600:1		211.2x158.4			
10.4	LQ104V1LG64	SHA	640x480	450cd/m²	600:1		211.2x158.4			
10.4	LQ104V1DW02	SHA	640x480	380cd/m²	450:1		211.2x158.4			
10.4	LTM10C210	TOSH	640x480	400cd/m²	250:1	45/45 55/55	211.2x158.4	50,000	T	
10.4	LTM10C209A	TOSH	640x480	350cd/m²	250:1	55/55 40/35				
10.4	LTD104C11S	TOSH	640x480	400cd/m²	300:1	60/60 40/50				
10.4	G104SN02 V1	AUO	800x600	400cd/m²	500:1	70/70 60/60	211.2x158.4	2xCCFL		
10.4	G104SN02 V2	AUO	800x600	400cd/m²	700:1	80/80 70/70	211.2x158.4	LED Backlight		
10.4	G104SN02	AUO	800x600	400cd/m²	500:1	60/60 50/50	211.2x158.4	50,000	T	
10.4	G104SN05	AUO	800x600	1,500cd/m²	500:1	40/60 60/60	211.2x158.4	50,000	T	
10.4	UB104S01	AUO	800x600	150cd/m²	250:1	15/35 45/45	211.2x158.4	20,000	T	
10.4	G104SN03 V1	AUO	800x600	230cd/m²	500:1	70/70 45/75	211.2x158.4	1xCCFL		
10.4	G104SN03 V2	AUO	800x600	180cd/m²	500:1	60/60 35/65				
10.4	G104SN03	AUO	800x600	230cd/m²	500:1	35/65 60/60	211.2x158.4	20,000	T	
10.4	B104SN02	AUO	800x600	400cd/m²	500:1	40/60 60/60	211.2x158.4	50,000	T	
10.4	B104SN02H	AUO	800x600	500cd/m²	350:1	40/60 60/60				
10.4	LP104S5-C1	LG	800x600	220cd/m²	400:1	40/40 55/55	211.2x158.4	20,000	T	
10.4	LB104S01-TL01	LG	800x600	250cd/m²	400:1	45/55 65/65				
10.4	LB104S01	LG	800x600	250cd/m²	400:1	70/70 50/50	211.2x158.4	20,000		
10.4	AA104SG02	MIT	800x600	400cd/m²	600:1	65/65 50/60		50,000		Wide Temp.
10.4	AA104SG01	MIT	800x600	400cd/m²	500:1	50/60 70/70		50,000		Wide Temp.
10.4	NL8060BC26-28	NEC	800x600	400cd/m²	700:1	85/85 85/85	211.2x158.4			
10.4	NL8060BC26-30D	NEC	800x600	400cd/m²	1000:1	80/80 80/80	211.2x158.4	CCFL		
10.4	NL8060BC26-30C	NEC	800x600	550cd/m²	900:1	80/80 80/80	211.2x158.4	CCFL		
10.4	NL8060BC26-17	NEC	800x600	280cd/m²	300:1	50/50 40/40				
10.4	NL8060BC26-27	NEC	800x600	400cd/m²	700:1	85/85 85/85				
10.4	T-51944D104J-FW-A-AA	OPT	800x600	400cd/m²	500:1	70/70 50/60				
10.4	PD104SL3	PVI	800x600	160cd/m²	400:1	45/45 40/15	211.2x158.4	40,000	T	
10.4	PD104SL5	PVI	800x600	350cd/m²	400:1	55/40 60/60	211.2x158.4	40,000	T	
10.4	LTN104S02-L01	SAM	800x600	230cd/m²	300:1	50/50 60/60	211.2x158.4	20,000	T	
10.4	LTA104S1-L01	SAM	800x600	350cd/m²	150:1	45/45 60/60	211.2x158.4	30,000	T	
10.4	LQ104S1LG31	SHA	800x600	350cd/m²	500:1	50/60 70/70	211.2x158.4	50,000	T	
10.4	LQ104V1DG21	SHA	800x600	350cd/m²	300:1	40/70 70/70	211.2x158.4	50,000	T	
10.4	LQ104S1DG21	SHA	800x600	350cd/m²	300:1	70/70 40/70	211.2x158.4			
10.4	LQ104S1DG61	SHA	800x600	450cd/m²	600:1	50/60 70/70	211.2x158.4			
10.4	LQ104S1LG41	SHA	800x600	370cd/m²	450:1	50/60 70/70	211.2x158.4			
10.4	LQ104S1LG21	SHA	800x600	350cd/m²	300:1	40/70 70/70	211.2x158.4			
10.4	LQ104S1LG61	SHA	800x600	450cd/m²	600:1	50/60 70/70	211.2x158.4			
11.6	B116XW01	AUO	1366x768	200cd/m²	500:1	45/45 25/25	256.1x144.0	LED Backlight		
11.6	CLAA116WT01	CPT	1366x768	200cd/m²	500:1					LVDS
11.6	CLAA116WA03	CPT	1366x768	200cd/m²	500:1					LVDS

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
11.6	CLAA116WA01	CPT	1366x768	200cd/m ²	500:1					LVDS
11.6	LP116WH1	LG	1366x768	200cd/m ²	300:1	20/20 40/40	256.13x144.0			
12.0	TX31D50VM2BAA	HIT	800x480	350cd/m ²	350:1	60/60 50/60				
12.1	G121X1	CMO	1024x768	450cd/m ²	700:1	80/80 80/80	245.76x184.32	50,000		Wide Temp.
12.1	G121X1-L01	CMO	1024x768	450cd/m ²	700:1	80/80 80/80	245.76x184.32	50,000		
12.1	N121X5	CMO	1024x768	170cd/m ²	500:1	20/45 45/45				
12.1	HT121X01	HYD	1024x768	150cd/m ²	200:1	45/45 20/50	245.76x184.32	1xCCFL		
12.1	HT121X01-101	HYD	1024x768	150cd/m ²	300:1	45/45 20/40	245.76x184.32	1xCCFL		
12.1	HT12X21-100	HYD	1024x768	150cd/m ²	450:1	80/80 80/80	245.8x184.3	10,000	T	
12.1	HT12X12-100	HYD	1024x768	150cd/m ²	200:1	15/30 45/45	245.8x184.3	15,000	T	
12.1	HT12X13	HYD	1024x768	150cd/m ²	300:1	45/45 20/50	245.8x184.3	1xCCFL	T	slim
12.1	HT12X13-100	HYD	1024x768	150cd/m ²	250:1	20/40 45/45	245.8x184.3	15,000	T	
12.1	HT12X14-100	HYD	1024x768	150cd/m ²	250:1	20/40 45/45	245.8x184.3	15,000	T	
12.1	HT12X21	HYD	1024x768	180cd/m ²	450:1	90/90 90/90	245.6x184.3	1xCCFL		Wide viewing angle
12.1	HV121X03	HYD	1024x768	195cd/m ²	500:1	89/89 89/89	245.76x184.32	CCFL		
12.1	HV121X02	HYD	1024x768	180cd/m ²	800:1	90/90 90/90				
12.1	IAXG02C	ID	1024x768	150cd/m ²	250:1	15/30 40/40	245.75x184.32	30,000	T	
12.1	AA121XH01	MIT	1024x768	320cd/m ²	550:1	65/65 75/45	245.76x184.32	50,000		
12.1	AA121XH03	MIT	1024x768	320cd/m ²	550:1	45/75 65/65	245.76x184.32	50,000		
12.1	AA121XH04	MIT	1024x768	320cd/m ²	600:1	60/60 45/75	245.76x184.32	50,000		
12.1	AA121XH05	MIT	1024x768	280cd/m ²	400:1	70/80 85/85	245.76x184.32	50,000		
12.1	AA121XH02	MIT	1024x768	280cd/m ²	400:1	70/80 85/85	245.76x184.32	50,000		
12.1	AA121XJ02	MIT	1024x768	1000cd/m ²	700:1	60/60 45/75		4xCCFL		High Brightness
12.1	AA121XK01	MIT	1024x768	500cd/m ²	600:1	80/80 60/80		LED Backlight		
12.1	AA121XJ01	MIT	1024x768	1000cd/m ²	600:1	45/75 65/65	245.76x184.32	50,000		High Brightness
12.1	AA121XH01	MIT	1024x768	320cd/m ²	550:1	45/75 65/65				Wide Temp.
12.1	NL10276BC24-13C	NEC	1024x768	400cd/m ²	600:1	70/70 45/55				
12.1	NL10276BC24-13	NEC	1024x768	400cd/m ²	600:1	70/70 45/55				
12.1	T-55105D121J-FW-A-AAN	OPT	1024x768	1000cd/m ²	600:1	65/65 45/75				
12.1	T-55105D121J-FW-A-ABN	OPT	1024x768	1000cd/m ²	700:1	65/65 45/75				
12.1	T-51756D121J-FW-A-AA	OPT	1024x768	320cd/m ²	550:1	75/45 65/65				Wide Temp.
12.1	LVM121XSB-411	VER	1024x768	1000cd/m ²	400:1	80/80 80/80	245.8x184.3	40,000		High Brightness
12.1	LVM121XSB-411-L01	VER	1024x768	1200cd/m ²	400:1	80/80 80/80	245.8x184.3	50,000/LED Backl.		LED Backlight
12.1	LVM121XD-02	VER	1024x768	600cd/m ²	400:1	80/80 80/80	245.8x184.3	40,000		W. viewing
12.1	LVM121XSB-02	VER	1024x768	1000cd/m ²	400:1	80/80 80/80	245.8x184.3	40,000	T	High Brightness
12.1	HX121WX1	HYD	1024x800	300cd/m ²	600:1	90/90 90/90	261.12x163.20	LED Backlight		
12.1	AA121TA01	MIT	1024x800	400cd/m ²	600:1	80/60 80/80		50,000		W. viewing angle
12.1	B121EW01	AUO	1280x800	200cd/m ²	400:1	40/40 20/40	261.1x163.2			
12.1	B121EW03	AUO	1280x800	200cd/m ²	400:1	40/40 20/40	261.1x163.2			
12.1	B121EW04	AUO	1280x800	220cd/m ²	700:1	40/40 20/40	261.1x163.2			
12.1	B121EW07 V0	AUO	1280x800	200cd/m ²	400:1	40/40 20/40	261.1x163.2			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
12.1	B121EW01 V1	AUO	1280x800	170cd/m²	300:1	40/40 20/40				
12.1	N121I3	CMO	1280x800	200cd/m²	500:1	20/45 45/45				
12.1	HT121WX2	HYD	1280x800	200cd/m²	200:1	40/40 20/40	261.12x163.20	1xCCFL		
12.1	HV121WX4	HYD	1280x800	200cd/m²	500:1	90/90 90/90	261.12x163.20	CCFL		
12.1	HV121WX5	HYD	1280x800	220cd/m²	500:1	90/90 90/90	261.12x163.20	LED Backlight		
12.1	HV121WX6	HYD	1280x800	220cd/m²	500:1	90/90 90/90	261.12x163.20	LED Backlight		
12.1	HV121WX1	HYD	1280x800	200cd/m²	450:1	89/89 89/89				
12.1	LP121WX3	LG	1280x800	200cd/m²	500:1	25/25 45/45	261.1x163.2	LED Backlight		
12.1	LP121WX1	LG	1280x800	200cd/m²	400:1	25/25 45/45	261.1x163.2			
12.1	AA121TA01-G1	MIT	1280x800	400cd/m²	600:1	80/80 80/60		2xCCFL		
12.1	AA121TC01	MIT	1280x800	1000cd/m²	600:1	80/80 80/60		2xCCFL		
12.1	AA121TB01	MIT	1280x800	400cd/m²	600:1	80/80 80/60		2xCCFL		
12.1	LTN121W	SAM	1280x800	180cd/m²	300:1	60/60 40/60				
12.1	HV121P01	HYD	1400x1050	190cd/m²	500:1	90/90 90/90	245.7x184.275	CCFL		
12.1	HSD121MV11-A	HAN	640x480	450cd/m²	500:1	70/70 70/60				
12.1	TSC1WA15-01	TOPS	800x480	450cd/m²	400:1	65/65 70/70	266.4x149.76	30,000		
12.1	G121SN01 V3	AUO	800x600	400cd/m²	500:1	80/80 55/55	246.0x184.5			Wide Temp.
12.1	G121SN01 V2	AUO	800x600	400cd/m²	500:1	70/70 60/50	246.0x184.5			
12.1	G121SN01 V1	AUO	800x600	200cd/m²	200:1	70/70 60/50		CCFL		Sunlight readable
12.1	G121SN01 V4	AUO	800x600	450cd/m²	700:1	80/80 70/70	246.0x184.5	LED Backlight		
12.1	G121SN01	AUO	800x600	400cd/m²	500:1	40/60 60/60				
12.1	G121S1	CMO	800x600	450cd/m²	1000:1	85/85 85/85	246.0x184.5			W.Temp/S.Slim
12.1	LB121S03-TL01	LG	800x600	400cd/m²	500:1	65/65 50/60	246.0x184.5	50,000	T	
12.1	LB121S02-A2	LG	800x600	300cd/m²	200:1	40/55 60/60	246.0x184.5	50,000	T	
12.1	LB121S02	LG	800x600	300cd/m²	200:1	60/60 50/50				
12.1	LB121S03	LG	800x600	400cd/m²	500:1	70/70 55/55				
12.1	AA121SR01	MIT	800x600	450cd/m²	600:1	80/80 80/60		50,000		
12.1	AA121SR02	MIT	800x600	450cd/m²	600:1	80/80 80/60		50,000		
12.1	AA121SL08	MIT	800x600	400cd/m²	600:1	45/75 60/60		50,000		
12.1	AA121SL09	MIT	800x600	400cd/m²	500:1	45/75 65/65		50,000		Wide Temp.
12.1	AA121SL10	MIT	800x600	400cd/m²	600:1	45/75 60/60		50,000		Wide Temp.
12.1	AA121SL11	MIT	800x600	350cd/m²	400:1	70/80 80/80		50,000		W. viewing angle
12.1	AA121SN01	MIT	800x600	1000cd/m²	600:1	45/75 65/65		50,000		High Brightness
12.1	AA121SN03	MIT	800x600	1500cd/m²	650:1	45/75 65/65		50,000		High Brightness
12.1	AA121SN04	MIT	800x600	1500cd/m²	700:1	60/60 45/75		4xCCFL		High Brightness
12.1	AA121SN02	MIT	800x600	1000cd/m²	700:1	45/75 60/60		50,000		Wide Temp.
12.1	AA121SL03	MIT	800x600	350cd/m²	500:1	45/75 65/65	246.0x184.5	50,000	T	
12.1	AA121SM02	MIT	800x600	400cd/m²	500:1	65/65 45/75		LED Backlight		
12.1	AA121SP07	MIT	800x600	450cd/m²	600:1	80/80 60/80		2xCCFL		
12.1	AA121SP06	MIT	800x600	450cd/m²	600:1	80/80 60/80		2xCCFL		
12.1	AA121SL06	MIT	800x600	350cd/m²	600:1	45/75 65/65				Wide Temp.

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
12.1	AA121SL01	MIT	800x600	350cd/m²	350:1	60/60 40/50				
12.1	AA121SL02	MIT	800x600	400cd/m²	500:1	45/75 65/65				Wide Temp.
12.1	NL8060BC31-41D	NEC	800x600	400cd/m²	600:1	80/60 80/80	246.0x184.5			
12.1	NL8060BC31-32	NEC	800x600	400cd/m²	600:1	45/55 70/70	246.0x184.5			
12.1	NL8060BC31-41C	NEC	800x600	550cd/m²	600:1	80/60 80/80	246.0x184.5	CCFL		
12.1	NL8060BC31-36	NEC	800x600	1100cd/m²	600:1	45/55 70/70	246.0x184.5			
12.1	NL8060BC31-47D	NEC	800x600	450cd/m²	900:1	80/80 80/80	246.0x184.5	LED Backlight		
12.1	NL8060BC31-42	NEC	800x600	400cd/m²	600:1	80/60 80/80	246.0x184.5			Clear
12.1	NL8060BC31-42D	NEC	800x600	400cd/m²	600:1	80/60 80/80	246.0x184.5			Anitglare
12.1	NL8060BC31-20	NEC	800x600	250cd/m²	400:1	80/80 80/80				
12.1	NL8060BC31-17	NEC	800x600	350cd/m²	350:1	40/50 55/55	246x184.5		T	
12.1	NL8060B31-28D	NEC	800x600	350cd/m²	600:1	70/70 45/55				
12.1	NL8060BC31-17D	NEC	800x600	350cd/m²	350:1	55/55 40/50				
12.1	NL8060BC31-27	NEC	800x600	400cd/m²	500:1	70/70 45/55				
12.1	T-52017D121J-FW-A-AA	OPT	800x600	1000cd/m²	650:1	65/65 45/75				
12.1	T-52017D121J-FW-A-ABN	OPT	800x600	1000cd/m²	700:1	65/65 45/75				
12.1	T-51512D121J-FW-A-AB	OPT	800x600	350cd/m²	350:1	60/60 40/50				
12.1	T-51866D121J-FW-A-AA	OPT	800x600	350cd/m²	500:1	65/65 45/75				
12.1	T-51866D121J-FW-A-ABN	OPT	800x600	350cd/m²	600:1	65/65 45/75				
12.1	T-51512D121J-FW-A-AE	OPT	800x600	350cd/m²	400:1	80/80 70/80				
12.1	T-51512D121J-FW-A-AC	OPT	800x600	400cd/m²	500:1	65/65 45/75				
12.1	LTM121S1-T01	SAM	800x600	300cd/m²	300:1	50/50 60/60	246x184.5	40,000	T	
12.1	LQ121S1DG11	SHA	800x600	250cd/m²	300:1	50/60 70/70	246x184.5	50,000	T	
12.1	LQ121S1DG31	SHA	800x600	300cd/m²	300:1	45/55 60/60	246x184.5	50,000	T	
12.1	LQ121S1DG41	SHA	800x600	370cd/m²	450:1	50/60 70/70	246x184.5			
12.1	LQ121S1LG41	SHA	800x600	350cd/m²	300:1	70/70 50/60	246x184.5			
12.1	LQ121S1DG61	SHA	800x600	450cd/m²	600:1		246x184.5			
12.1	LQ121S1LG61	SHA	800x600	350cd/m²	300:1		246x184.5			
12.1	LQ121S1DG65	SHA	800x600	450cd/m²	600:1	50/60 70/70	246x184.5			
12.1	LQ121S1DG64	SHA	800x600	450cd/m²	600:1		246x184.5			
12.1	LQ121S1LG64	SHA	800x600	450cd/m²	600:1		246x184.5			
12.1	LQ121S7LY01	SHA	800x600	200cd/m²	400:1	80/80 80/80	246x184.5			
12.1	LQ121S1LW01	SHA	800x600	250cd/m²	800:1	85/85 85/85	246x184.5			
12.1	LTD121C31S-12	TOSH	800x600	250cd/m²	400:1	60/60 60/40				
12.1	LTD121C32S	TOSH	800x600	250cd/m²	450:1	60/60 50/50				
12.1	LTD121C30S	TOSH	800x600	350cd/m²	500:1	70/70 60/60				
12.1	LTD121C33S	TOSH	800x600	350cd/m²	500:1	70/70 60/60				
12.1	LTM12C285	TOSH							T	
13.3	B133EW01	AUO	1280x800	250cd/m²	400:1	45/45 30/25	286.1x178.8			
13.3	N13311	CMO	1280x800	250cd/m²	500:1	20/45 45/45				
13.3	HV133WX1	HYD	1280x800	300cd/m²	500:1	90/90 90/90	286.1x178.8	LED Backlight		LVDS

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
13.3	LP133WX2	LG	1280x800	275cd/m²	400:1	25/25 45/45	286.1x178.8	LED Backlight		
13.3	LP133WX1	LG	1280x800	200cd/m²	400:1	25/25 45/45	286.1x178.8			
13.3	B133XW01	AUO	1366x768	220cd/m²	500:1	45/45 25/25	293.4x165.0	LED Backlight		
13.3	B133XW02	AUO	1366x768	220cd/m²	500:1	45/45 30/30	293.4x165.0	LED Backlight		
13.3	CLAA133WA01	CPT	1366x768	200cd/m²	600:1					
13.3	LP133WH1	LG	1366x768	200cd/m²	400:1	25/25 45/45	293.42x164.97	LED Backlight		
14.0	B140XW01	AUO	1366x768	200cd/m²	500:1	45/45 25/25	309.4x174.0	LED Backlight		
14.0	B140XW02	AUO	1366x768	220cd/m²	500:1	45/45 25/25		LED Backlight		
14.0	CLAA140WD14	CPT	1366x768	220cd/m²	600:1			LED Backlight		
14.0	CLAA140WD12	CPT	1366x768	220cd/m²	600:1			LED Backlight		
14.0	LP140WH1	LG	1366x768	220cd/m²	600:1	60/60 70/70	309.4x173.95	LED Backlight		
14.0	LP140WD1	LG	1600x900	250cd/m²	600:1	60/60 50/50	309.6x174.15	LED Backlight		
14.0	T140VN01	AUO	640x480	450cd/m²	500:1	85/85 85/85	283.2x212.4	50,000	T	
14.1	B141XG09 V3	AUO	1024x768	200cd/m²	300:1	40/40 30/30	285.7x214.3			
14.1	N141XA	CMO	1024x768	200cd/m²	600:1	20/45 45/45				
14.1	HT14X19-300	HYD	1024x768	150cd/m²	200:1	45/45 15/35	285.7x214.3	15,000	T	
14.1	B141EW02	AUO	1280x768	200cd/m²	400:1	45/45 30/35	303.36x189.6			
14.1	LP141WX3	LG	1280x768	200cd/m²	400:1	25/25 45/45	303.7x189.8			
14.1	LP141WX1	LG	1280x768	200cd/m²	400:1	25/25 45/45				
14.1	N141I3	CMO	1280x800	220cd/m²	300:1	20/45 45/45				
14.1	CLAA141WB02	CPT	1280x800	200cd/m²	450:1					
14.1	CLAA141WB05	CPT	1280x800	200cd/m²	450:1					
14.1	HT141WX1	HYD	1280x800	200cd/m²	300:1	45/45 20/45	303.36x189.6	1xCCFL		
14.1	LP141WX5	LG	1280x800	200cd/m²	400:1	25/25 45/45	303.7x189.8	LED Backlight		
14.1	AA141TA04-G1	MIT	1280x800	550cd/m²	700:1	80/80 80/70		4xCCFL		
14.1	AA141TB01	MIT	1280x800	1000cd/m²	600:1	80/80 80/70		4xCCFL		High Brightness
14.1	AA141TA01	MIT	1280x800	400cd/m²	700:1	70/80 80/80		50,000		W. viewing angle
14.1	HT141P12-100	HYD	1400x1050	150cd/m²	200:1	45/45 15/35	285.6x214.3	1xCCFL		Slim
14.1	LTN141P4	SAM	1400x1050	175cd/m²	500:1	25/45 45/45	285.6x214.2			
14.1	B141PW01	AUO	1440x900	220cd/m²	400:1	45/45 30/35	303.5x189.7			
14.1	LP141WP2	LG	1440x900	300cd/m²	500:1	25/25 45/45	303.3x189.5			
14.1	LP141WP1	LG	1440x900	220cd/m²	400:1	25/25 45/45	303.7x189.8			
15.0	NL10276BC30-10	NEC	1024x762	250cd/m²	450:1	40/60 60/60	304.128x228.096		T	
15.0	M150XN07	AUO	1024x768	250cd/m²	400:1	40/60 60/60	304.1x228.1	30,000	T	
15.0	G150XG03	AUO	1024x768	250cd/m²	500:1	60/60 70/70				
15.0	M150XN07 V2	AUO	1024x768	250cd/m²	500:1	60/60 70/70				
15.0	G150XG01	AUO	1024x768	350cd/m²	500:1	40/60 60/60	304.1x228.1	50,000	T	
15.0	G150XG02 V0	AUO	1024x768	550cd/m²	500:1	70/70 60/60	304.128x228.096	4xCCFL	T	
15.0	G150XG01 V1	AUO	1024x768	350cd/m²	700:1	70/70 60/60	304.1x228.1	2xCCFL		
15.0	G150XG02	AUO	1024x768	550cd/m²	500:1	70/70 60/60	304.128x228.096	50,000	T	
15.0	G150XG01 V0	AUO	1024x768	350cd/m²	500:1	40/60 60/60	304.1x228.1	50,000	T	

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
15.0	B150XG02 V4	AUO	1024x768	180cd/m²	300:1	40/40 20/20	304.1x228.1			
15.0	G150XG03 V2	AUO	1024x768	250cd/m²	700:1	70/70 60/60	304.1x228.1	2xCCFL		
15.0	T150XG01 V0	AUO	1024x768	450cd/m²	500:1	80/80 80/55				
15.0	T150XG01 V1	AUO	1024x768	450cd/m²	500:1	80/80 80/55				
15.0	M150XN04	AUO	1024x768	500cd/m²	400:1	60/60 70/70	304.1x228.1	30,000	T	
15.0	N150X7	CMO	1024x768	500cd/m²	600:1	60/60 70/70				
15.0	M150X2-T06(MVA)	CMO	1024x768	350cd/m²	500:1	85/85 85/85	304.1x228.1	50,000	T	
15.0	V150X1	CMO	1024x768	400cd/m²	700:1	40/60 60/60				
15.0	G150X1	CMO	1024x768	450cd/m²	700:1	80/80 80/80	304.128x228.096			W. Temp./V.Angle
15.0	M150X3-L04	CMO	1024x768	50cd/m²	300:1	40/60 60/60	304.1x228.1	50,000	T	
15.0	CLAA150XP07FQ	CPT	1024x768	450cd/m²	500:1					
15.0	CLAA150XP07Q	CPT	1024x768	450cd/m²	500:1					
15.0	CLAA150XP01Q	CPT	1024x768	250cd/m²	500:1					
15.0	HSD150MX41-A	HAN	1024x768	200cd/m²	250:1	60/60 40/45				
15.0	HSD150MX15-A	HAN	1024x768	250cd/m²	600:1	65/65 45/55				
15.0	HSD150MX17	HAN	1024x768	250cd/m²	600:1	65/65 45/55				
15.0	HSD150SXA2-A	HAN	1024x768	250cd/m²	600:1	65/65 45/55				
15.0	HSD150MX19	HAN	1024x768	440cd/m²	500:1	75/75 60/70				
15.0	HSD150SX89	HAN	1024x768	450cd/m²	500:1	75/75 65/70				
15.0	HSD150MX15-B	HAN	1024x768	250cd/m²	450:1	45/55 60/60	304.1x228.1	30,000	T	
15.0	HSD150SX84-G	HAN	1024x768	250cd/m²	450:1	45/55 60/60	304.1x228.1	30,000	T	
15.0	HSD150MX17-A	HAN	1024x768	250cd/m²	450:1	45/55 60/60	308 x 234	30,000	T	
15.0	TX38D01VM1AAA	HIT	1024x768	350cd/m²	500:1	60/60 55/45				
15.0	TX38D07VM1AAA	HIT	1024x768	350cd/m²	500:1	60/60 60/50				
15.0	TX38D88VC1GAA	HIT	1024x768	430cd/m²	600:1	80/80 50/50				
15.0	HM15X11-200	HYD	1024x768	220cd/m²	250:1	55/55 35/55				
15.0	HT150X02	HYD	1024x768	250cd/m²	500:1	75/75 70/60				
15.0	HT15X23-110	HYD	1024x768	280cd/m²	400:1	89/89 89/89	304.1x228.1	50,000	T	
15.0	HT15X23	HYD	1024x768	280cd/m²	500:1	90/90 90/90				
15.0	HT15X23-100	HYD	1024x768	280cd/m²	450:1	89/89 89/89				
15.0	HT15X15	HYD	1024x768	400cd/m²	500:1	65/65 45/65	304.128x228.096			
15.0	HT15X15-D01	HYD	1024x768	400cd/m²	500:1	45/65 65/65	304.1x228.1	35,000	T	
15.0	HT15X15-D00	HYD	1024x768	450cd/m²	500:1	65/65 45/65	304.1x228.1		T	
15.0	N150X4-L01	ID	1024x768	200cd/m²	400:1	85/85 85/85	304.128 x 228.096	30,000	T	
15.0	N150X4-L14	ID	1024x768	250cd/m²	400:1	85/85 85/85	304.128 x 228.096	30,000	T	
15.0	LM150X08-A4	LG	1024x768	250cd/m²	400:1	45/55 65/65	304.1x228.1	40,000	T	
15.0	LC150X01-SL01	LG	1024x768	410cd/m²	450:1	89/89 89/89	332.8x262.8	50,000	T	
15.0	LC150X02-A4	LG	1024x768	450cd/m²	400:1	45/55 65/65	304.1x228.1	50,000	T	
15.0	LC150X02-TL01	LG	1024x768	450cd/m²	500:1	65/65 45/55	332.8x262.8	50,000	T	
15.0	LC150X02	LG	1024x768	450cd/m²	600:1	50/50 65/65				
15.0	LC150X01-A3	LG	1024x768	450cd/m²	400:1	85/85 85/85				

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
15.0	LC150X01	LG	1024x768	430cd/m²	500:1	89/89 89/89	304.1x262.8			
15.0	LP150X08	LG	1024x768	200cd/m²	250:1	25/25 45/45	304.1x228.1			
15.0	LP150X09	LG	1024x768	300cd/m²	300:1	25/25 45/45	304.1x228.1			
15.0	LM150X08	LG	1024x768	250cd/m²	800:1	70/70 70/70	304.1x228.1			
15.0	AA150XT11	MIT	1024x768	1500cd/m²	800:1	80/80 60/80		LED Backlight		High Brightness
15.0	AA150XT01	MIT	1024x768	800cd/m²	800:1	80/80 60/80		LED Backlight		
15.0	AA150XR01	MIT	1024x768	1500cd/m²	650:1	70/70 50/60		6xCCFL		High Brightness
15.0	AA150XN01	MIT	1024x768	250cd/m²	450:1	75/75 50/60		50,000		
15.0	AA150XC01	MIT	1024x768	300cd/m²	450:1	50/60 75/75	304.1x228.1	50,000	T	
15.0	AA150XN08	MIT	1024x768	800cd/m²	600:1	75/75 50/60		50,000		High Brightness
15.0	AA150XN03	MIT	1024x768	350cd/m²	450:1	75/75 50/60		50,000		
15.0	AA150XN04	MIT	1024x768	400cd/m²	350:1	70/80 85/85		50,000		Wide Temp.
15.0	AA150XC03	MIT	1024x768	400cd/m²	500:1	75/75 50/60				
15.0	AA150XN02	MIT	1024x768	450cd/m²	450:1	50/60 75/75		50,000		Wide Temp.
15.0	NL10276BC30-15	NEC	1024x768	250cd/m²	450:1	60/60 40/60				
15.0	NL10276BC30-24D	NEC	1024x768	320cd/m²	450:1	60/60 50/50				
15.0	NL10276BC30-34D	NEC	1024x768	400cd/m²	600:1	80/80 80/80	304.128x228.096	LED Backlight		
15.0	NL10276BC30-32D	NEC	1024x768	250cd/m²	500:1	80/80 80/80				
15.0	NL10276BC30-17	NEC	1024x768	350cd/m²	700:1	85/85 85/85				
15.0	NL10276AC30-07	NEC	1024x768	400cd/m²	300:1	85/85 85/85				
15.0	NL10276BC30-09	NEC	1024x768	400cd/m²	400:1	60/60 50/50				
15.0	NL10276BC30-33D	NEC	1024x768	350cd/m²	500:1	80/80 80/80				
15.0	NL10276BC30-18C	NEC	1024x768	600cd/m²	600:1	80/80 80/80				
15.0	NL10276BC30-18	NEC	1024x768	500cd/m²	500:1	80/80 80/80				
15.0	T-51863D150J-FW-A-AA	OPT	1024x768	250cd/m²	450:1	75/75 50/60				
15.0	T-51511D150-FW-A-AC	OPT	1024x768	300cd/m²	450:1	75/75 50/60				
15.0	T-51863D150J-FW-A-AD	OPT	1024x768	400cd/m²	350:1	85/85 70/80				
15.0	T-51511D150-FW-A-AD	OPT	1024x768	400cd/m²	450:1	75/75 50/60				
15.0	T-51863D150J-FW-A-AE	OPT	1024x768	450cd/m²	450:1	75/75 50/60				
15.0	T-51863D150J-FW-A-AB	OPT	1024x768	450cd/m²	450:1	75/75 50/60				
15.0	LTA15XH-L06	SAM	1024x768	400cd/m²	400:1	70/70 60/65	304.1x228.1	35,000		
15.0	LTM150XH-L01	SAM	1024x768	250cd/m²	300:1	50/60 65/65	304.1x228.1	25,000	T	
15.0	LTM150XO-L01	SAM	1024x768	250cd/m²	450:1	50/60 65/65	304.1x228.1	35,000	T	
15.0	LTM150X0	SAM	1024x768	250cd/m²	700:1	75/60 75/75				
15.0	LTM150XO-L0X	SAM	1024x768	250cd/m²	700:1	75/75 75/60				
15.0	LTM150XH-L06	SAM	1024x768	450cd/m²	400:1	70/70 50/60	304.1x228.1	50,000	T	
15.0	LTM150XH	SAM	1024x768	450cd/m²	400:1	70/70 60/65				
15.0	LQ150X1LG55	SHA	1024x768	350cd/m²	550:1	45/55 60/60	304.1x228.1			
15.0	LQ150X1LG45	SHA	1024x768	250cd/m²	550:1	45/55 60/60	304.1x228.1			
15.0	LQ150X1DG11	SHA	1024x768	200cd/m²	300:1	69/60 70/70	304.1x228.1	50,000	T	
15.0	LQ150X1LW71N	SHA	1024x768	250cd/m²	400:1	85/85 85/85	304.1x228.1	50,000	T	

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
15.0	LQ150X1DWF1	SHA	1024x768	250cd/m²	400:1	80/80 80/80	304.1x228.1			
15.0	LQ150X1LGN12A	SHA	1024x768	260cd/m²	350:1	60/60 45/55	304.1x228.1			
15.0	LQ150X1DW11	SHA	1024x768	300cd/m²	350:1	85/85 85/85	304.1x228.1	50,000	T	
15.0	LQ150X1LGB1	SHA	1024x768	600cd/m²	350:1	55/80 80/80	304.1x228.1			
15.0	LQ150X1LGB4	SHA	1024x768	600cd/m²	350:1		304.1x228.1			
15.0	LQ150X1LGN2A	SHA	1024x768	260cd/m²	350:1	55/80 80/80	304.1x228.1			
15.0	LQ150X1LGN2	SHA	1024x768	260cd/m²	350:1	55/80 40/40	304.1x228.1			
15.0	LQ150X1LGN2E	SHA	1024x768	350cd/m²	350:1		304.1x228.1			
15.0	LQ150X1LW72	SHA	1024x768	350cd/m²	600:1	85/85 85/85	304.1x228.1			
15.0	N150P5	CMO	1400x1050	200cd/m²	400:1	60/60 70/70				
15.0	HV150P01	HYD	1400x1050	200cd/m²	500:1	89/89 89/89				
15.0	N150P2-L04	ID	1400x1050	200cd/m²	250:1	15/30 40/40	304.5x228.375	30,000	T	
15.0	N150P3-L04	ID	1400x1050	200cd/m²	400:1	85/85 85/85	304.5x228.375	30,000	T	
15.0	LP150E06	LG	1400x1050	200cd/m²	300:1	45/45 60/60	304.1x228.1			
15.0	LP150E05/E06	LG	1400x1050	185cd/m²	300:1	60/60 45/45	317.3x241.5	10,000	T	
15.0	LTN15PG	SAM	1400x1050	200cd/m²	600:1	50/50 65/65	304.5x228.4			
15.0	HV150UX1	HYD	1600x1200	200cd/m²	500:1	89/89 89/89				
15.0	N150U3	ID	1600x1200	200cd/m²	400:1	85/85 85/85	304.8x228.6	30,000	T	
15.0	IAQX10	ID	2048x1536	150cd/m²	400:1	85/85 85/85	304.1x228.1	30,000	T	
15.0	IAQX10M	ID	2048x1536	200cd/m²	400:1	85/85 85/85	304.1x228.1	30,000	T	
15.0	V150V1	CMO	640x480	500cd/m²	800:1	88/88 88/88	305.28x228.96			
15.0	NL10276HC30-10E	NEC							T	
15.1	LC151X01-C3	LG	1024x768	400cd/m²	350:1	50/70 75/75	307.2x230.4	50,000	T	
15.3	NL12876BC26-28	NEC	1280x768	330cd/m²	1000:1	88/88 88/88	334.08x200.45			
15.3	NL12876BC26-25	NEC	1280x768	470cd/m²	700:1	85/85 85/85	334.08x200.45	50,000		
15.4	B154EW02 V1	AUO	1280x800	200cd/m²	400:1	40/40 20/20	331.2x207.0			
15.4	N154I2	CMO	1280x800	200cd/m²	400:1	20/45 45/45				
15.4	N154I4	CMO	1280x800	500cd/m²	1000:1	60/60 40/60				
15.4	N154I5	CMO	1280x800	300cd/m²	400:1	20/45 45/45				
15.4	CLAA154WB03A	CPT	1280x800	200cd/m²	1000:1					
15.4	CLAA154WB05	CPT	1280x800	200cd/m²	500:1					
15.4	CLAA154WB06	CPT	1280x800	350cd/m²	600:1					
15.4	TX39DXXDXXVMXXXX	HIT	1280x800	350cd/m²	500:1	60/60 60/50				
15.4	HT154WX1	HYD	1280x800	185cd/m²	300:1	65/65 40/60				
15.4	HT154WX3	HYD	1280x800	450cd/m²	500:1	65/65 40/60				
15.4	HT154WX2	HYD	1280x800	450cd/m²	500:1	75/75 65/65				
15.4	LP154WX7	LG	1280x800	220cd/m²	400:1	25/25 45/45	331.2x207.0			
15.4	LP154WX4	LG	1280x800	200cd/m²	400:1	25/25 45/45	331.2x207.0			
15.4	B154PW04 V0	AUO	1440x900	330cd/m²	400:1	70/70 60/60	331.5x207.2			
15.4	N154C1	CMO	1440x900	300cd/m²	500:1	60/60 70/70				
15.4	N154C3	CMO	1440x900	200cd/m²	500:1	20/45 45/45				

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
15.4	N154C4	CMO	1440x900	500cd/m²	500:1	60/60 70/70				
15.4	N154C5	CMO	1440x900	300cd/m²	500:1	20/45 45/45				
15.4	CLAA154WP01	CPT	1440x900	300cd/m²	600:1					
15.4	CLAA154WP05	CPT	1440x900	200cd/m²	600:1					
15.4	CLAA154WP07	CPT	1440x900	200cd/m²	500:					
15.4	CLAA154WP04	CPT	1440x900	250cd/m²	600:1					
15.4	LP154WP2	LG	1440x900	330cd/m²	500:1	55/55 60/60	331.4x207.1			
15.4	LP154WP1	LG	1440x900	250cd/m²	600:1	60/60 80/80	331.3x207.1			
15.4	N154Z1	CMO	1680x1050	200cd/m²	500:1	40/60 60/60				
15.4	LP154WE2	LG	1680x1050	200cd/m²	500:1	55/55 65/65	331.4x207.1			
15.4	LP154WU1	LG	1920x1200	210cd/m²	500:1	50/50 65/65	331.2x207.0			
15.6	B156XW02	AUO	1366x768	220cd/m²	500:1	45/45 25/25	344.2x193.5	LED Backlight		
15.6	B156XW03	AUO	1366x768	220cd/m²	500:1	45/45 25/25	344.2x193.5	LED Backlight		
15.6	M156XW01 V0	AUO	1366x768	250cd/m²	500:1	45/45 30/30	344.2x193.5	2xCCFL		
15.6	CLAA156WA11	CPT	1366x768	220cd/m²	600:1			LED Backlight		DisplayPort
15.6	CLAA156WA12	CPT	1366x768	220cd/m²	600:1			LED Backlight		LVDS
15.6	LP156WH2	LG	1366x768	220cd/m²	500:1	25/25 45/45	344.232x193.536	LED Backlight		
15.6	LM156WH1	LG	1366x768	200cd/m²	600:1	25/25 45/45	344.232x193.536			
15.6	LP156WD1	LG	1600x900	250cd/m²	600:1	50/50 60/60	344.232x193.536	LED Backlight		
15.6	LP156WF1	LG	1920x1080	310cd/m²	600:1	5/55 65/65	344.232x193.536	LED Backlight		
16.6	TX42D50VM1CAA	HIT	1024x768	350cd/m²	500:1	60/60 60/50				
16.6	TX42D30VM1CAA	HIT	1024x768	350cd/m²	500:1	60/60 60/50				
17.0	M170EN05	AUO	1280x1024	260cd/m²	450:1	70/70 70/70	337.9x270.3	50,000	T	
17.0	M170EN07	AUO	1280x1024	260cd/m²	450:1	70/70 70/70	337.9x270.3	50,000	T	
17.0	M170EG01 VG	AUO	1280x1024	250cd/m²	1000:1	80/80 80/80	337.9x270.3	2xCCFL		
17.0	M170EG01 VD	AUO	1280x1024	300cd/m²	800:1	80/80 80/80	337.9x270.3	50,000		W. viewing angle
17.0	M170EG01	AUO	1280x1024	260cd/m²	450:1	70/70 70/70				Ultra Slim
17.0	M170EG01 V5	AUO	1280x1024	260cd/m²	450:1	70/70 70/60				
17.0	M170EG01 V0	AUO	1280x1024	300cd/m²	500:1	60/60 70/70				
17.0	M170EU01 V0	AUO	1280x1024	300cd/m²	700:1	70/70 75/75				
17.0	M170EG01 V8	AUO	1280x1024	300cd/m²	500:1	70/70 70/60				
17.0	M170EG01 V7	AUO	1280x1024	300cd/m²	500:1	70/70 70/60				
17.0	M170EN06	AUO	1280x1024	400cd/m²	450:1	70/70 70/70	337.9x270.3	50,000	T	
17.0	M170EG01 V3	AUO	1280x1024	400cd/m²	500:1	70/70 70/60				
17.0	M170EG01 V9	AUO	1280x1024	420cd/m²	500:1	70/70 70/60				
17.0	M170E5	CMO	1280x1024	300cd/m²	800:1	85/85 80/80				
17.0	M170E7	CMO	1280x1024	300cd/m²	800:1	85/85 80/80				Super Slim
17.0	M170E7-L02	CMO	1280x1024	300cd/m²	800:1	80/80 85/85	337.92x270.34		T	Super Slim
17.0	CLAA170EA07P	CPT	1280x1024	300cd/m²	1000:1					
17.0	CLAA170ES03	CPT	1280x1024	300cd/m²	1000:1					
17.0	HSD170ME13-C	HAN	1280x1024	270cd/m²	500:1	70/70 70/60				

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
17.0	HSD170ME13	HAN	1280x1024	250cd/m²	450:1	70/60 70/70	337.92x270.336	30,000	T	
17.0	HT17E12-200	HYD	1280x1024	250cd/m²	430:1	65/65 80/80	337.9x270.3	50,000	T	
17.0	HT17E11-300	HYD	1280x1024	250cd/m²	500:1	75/75 55/75				
17.0	HT17E13-100	HYD	1280x1024	300cd/m²	450:1	65/65 75/75	337.9x270.3	50,000	T	
17.0	HT170EX1-101	HYD	1280x1024	300cd/m²	700:1	75/75 75/60				
17.0	HT170E01	HYD	1280x1024	300cd/m²	700:1	75/75 60/75				
17.0	HT170EX1	HYD	1280x1024	300cd/m²	700:1	75/75 75/60				
17.0	HM17E13	HYD	1280x1024	300cd/m²	450:1	75/75 65/65				
17.0	LM170E01-A5	LG	1280x1024	250cd/m²	450:1	60/60 70/70	337.9x270.3	50,000	T	
17.0	LM170E01	LG	1280x1024	250cd/m²	600:1	70/70 75/65				
17.0	LM170E01-LTA1	LG	1280x1024	250cd/m²	600:1	70/70 75/65				
17.0	LM170E02	LG	1280x1024	300cd/m²	800:1	80/80 80/80	337.9x270.3			
17.0	LM170E03	LG	1280x1024	300cd/m²	800:1	80/80 85/85	337.9x270.3			
17.0	AA170EB01	MIT	1280x1024	550cd/m²	800:1	80/80 80/60		4xCCFL		
17.0	LTM170ET01	SAM	1280x1024	250cd/m²	1000:1	80/80 80/80		CCFL		
17.0	LTM170EX	SAM	1280x1024	300cd/m²	1000:1	80/80 80/80	337.9x270.3	50,000	T	
17.0	LTM170EX-L01	SAM	1280x1024	250cd/m²	500:1	75/75 75/60	337.9x270.3	50,000	T	
17.0	LTM170E6-L04	SAM	1280x1024	250cd/m²	600:1	89/89 89/89	337.9x270.3	50,000	T	
17.0	LTM170E8-L01	SAM	1280x1024	250cd/m²	600:1	89/89 89/89	337.9x270.3	50,000	T	
17.0	LTM170EU-L01	SAM	1280x1024	270cd/m²	350:1	70/70 60/60				
17.0	LTM170EU	SAM	1280x1024	400cd/m²	1000:1	80/80 80/80	337.9x270.3			
17.0	LTM170E8	SAM	1280x1024	280cd/m²	1500:1	90/90 90/90	337.9x270.3			
17.0	LTM170EU-L21	SAM	1280x1024	300cd/m²	700:1	75/75 75/60	337.9x270.3	10,000	T	
17.0	LTM170EX	SAM	1280x1024	300cd/m²	1000:1	80/80 80/80				
17.0	CLAA170WA02	CPT	1280x720	250cd/m²	500:1					
17.0	CLAA170WA02C	CPT	1280x720	250cd/m²	500:1					
17.0	M170XW01	AUO	1280x768	450cd/m²	600:1	89/89 89/89				
17.0	M170XW01 V3	AUO	1280x768	450cd/m²	800:1	85/85 85/85				
17.0	M170XW01 V2	AUO	1280x768	450cd/m²	800:1	85/85 85/85				
17.0	T170XW01 V1	AUO	1280x768	500cd/m²	600:1	85/85 85/85	370.6x222.3	50,000	T	W
17.0	LTM170W1	SAM	1280x768	400cd/m²	450:1	70/70 60/60				
17.0	LTM170W1-L01	SAM	1280x768	450cd/m²	400:1	50/60 70/70	370.6x222.3	50,000	T	
17.0	LTA170WP-L01	SAM	1280x768	450cd/m²	500:1	85/85 85/85	370.6x222.3	50,000	T	
17.0	LTA170W2-L01	SAM	1280x768	450cd/m²	800:1	85/85 85/85				
17.0	LC170WXN	LG	1366x768	500cd/m²	800:1	89/89 89/89	372.918x209.664			
17.0	B170PW03	AUO	1440x900	200cd/m²	400:1	70/70 60/60	367.2x229.5			
17.0	B170PW07	AUO	1440x900	500cd/m²	700:1	70/70 60/60	367.2x229.5			
17.0	N170C2	CMO	1440x900	200cd/m²	400:1	20/45 45/45				
17.0	N170C3	CMO	1440x900	400cd/m²	600:1	60/60 70/70				
17.0	B170UW02	AUO	1920x1200	400cd/m²	600:1	70/70 60/60	367.2x229.5			
17.0	B170UW02 V0	AUO	1920x1200	400cd/m²	600:1	70/70 60/60	367.2x229.5			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
17.1	LC171W03	LG	1280x1024	550cd/m²	800:1	90/90 90/90				
17.1	LC171W03-A4	LG	1280x768	450cd/m²	400:1	88/88 88/88	372.5x223.5	50,000	T	
17.1	LC171W03-C4	LG	1280x768	450cd/m²	600:1	89/89 89/89				
17.1	LM171WX3	LG	1440x900	250cd/m²	800:1	65/85 85/85	367.2x229.5			
17.1	LP171WPA	LG	1440x900	320cd/m²	600:1	25/25 55/55	367.2x229.5	LED Backlight		
17.1	LP171WP7	LG	1440x900	450cd/m²	800:1	60/60 70/70	367.2x229.5			
17.1	LP171WP4	LG	1440x900	200cd/m²	500:1	25/25 45/45	367.2x229.5			
17.1	LP171WL7	LG	1440x900	500cd/m²	700:1	60/60 70/70				
17.1	LP171WE2	LG	1680x1050	300cd/m²	600:1	50/50 65/65	367.42x229.64			
17.1	LP171WU1-A4	LG	1920x1200	180cd/m²	350:1	65/65 50/50	382.7x245.0	10,000	T	
17.1	LP171WU1	LG	1920x1200	260cd/m²	600:1	60/60 70/70	367.2x229.5			
17.3	B173RW01	AUO	1440x900	220cd/m²	500:1	45/45 25/25	382.1x214.9	LED Backlight		
17.3	CLAA173UA01	CPT	1600x900	220cd/m²	600:1					LVDS
17.3	CLAA173UA12	CPT	1600x900	220cd/m²	600:1			LED Backlight		DisplayPort
17.3	LP173WD1	LG	1600x900	200cd/m²	600:1	25/25 45/45	381.8x214.8	LED Backlight		
17.3	LP173WF1	LG	1920x1080	300cd/m²	600:1	50/50 60/60	381.888x214.812	LED Backlight		
17.5	AA175TB01	MIT	1280x768	400cd/m²	500:1	56/60 75/75		50,000		
18.0	LQ180E1DW28	SHA	1280x1024	200cd/m²	350:1	85/85 85/85	359.0x287.2	50,000	T	
18.0	LQ180E1LW31	SHA	1280x1024	220cd/m²	400:1	85/85 85/85	359.0x287.2	50,000	T	
18.1	F8598	CMO	1280x1024	270cd/m²	400:1	85/85 85/85	359x287.2			Medical
18.1	F8588	CMO	1280x1024	700cd/m²	550:1	85/85 85/85	359x287.2			Medical
18.1	HT18E22-200	HYD	1280x1024	210cd/m²	300:1	80/80 80/80	359.0x287.2	30,000	T	
18.1	ITSX98E	ID	1280x1024	270cd/m²	400:1	85/85 85/85	359.0x287.2	30,000	T	
18.1	ITSX88E	ID	1280x1024	700cd/m²	550:1	85/85 85/85	359.0x287.2	30,000	T	
18.1	ISTX88	ID	1280x1024	700cd/m²	550:1	85/85 85/85				
18.1	LM181E06-A4M1/D4	LG	1280x1024	250cd/m²	350:1	80/80 80/80	359.0x287.2	40,000	T	
18.5	M185XW01 V2	AUO	1366x768	250cd/m²	1000:1	85/85 80/80	409.8x230.4	2xCCFL		
18.5	CLAA185WA05	CPT	1366x768	200cd/m²	800:1					
18.5	CLAA185WA03	CPT	1366x768	250cd/m²	1000:1					
18.5	CLAA185WA02	CPT	1366x768	300cd/m²	1000:1					
18.5	CLAA185WA04	CPT	1366x768	250cd/m²	1000:1					
18.5	LM185WH1	LG	1366x768	300cd/m²	1000:1	80/80 85/85	409.8x230.4			
18.5	LM185WH2	LG	1366x768	250cd/m²	1000:1	80/80 85/85	409.8x230.4			
19.0	M190EN02	AUO	1280x1024	250cd/m²	700:1	70/70 70/70	376.3x301.1	50,000	T	
19.0	M190EN03	AUO	1280x1024	250cd/m²	800:1	85/85 85/85				
19.0	M190EN04	AUO	1280x1024	250cd/m²	450:1	65/65 65/65				
19.0	M190EN04 V5	AUO	1280x1024	270cd/m²	700:1	70/70 70/60				
19.0	M190EG02 V4	AUO	1280x1024	300cd/m²	800:1	80/80 80/80				
19.0	M190EG02 V1	AUO	1280x1024	300cd/m²	700:1	80/80 80/80				
19.0	M190EG01 V0	AUO	1280x1024	300cd/m²	1000:1	89/89 89/89				
19.0	M190EN04 V1	AUO	1280x1024	400cd/m²	500:1	70/70 70/70	376.3x301.1	50,000	T	

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
19.0	M190EN04 V7	AUO	1280x1024	400cd/m²	550:1	70/70 70/60				
19.0	R190E1	CMO	1280x1024	250cd/m²	1000:1	80/80 80/80				Medical
19.0	M190E5-L0G	CMO	1280x1024	250cd/m²	800:1	80/80 85/85	376.32x301.056			High Color Gamut
19.0	M190E05-L0E	CMO	1280x1024	300cd/m²	1000:1	80/80 80/80				
19.0	M190E5-L0E	CMO	1280x1024	300cd/m²	1000:1	80/80 80/80	410.4x256.5			
19.0	HSD190ME13-C	HAN	1280x1024	250cd/m²	500:1	70/70 70/60				
19.0	HSD190ME13-A	HAN	1280x1024	250cd/m²	500:1	70/70 70/60				
19.0	HSD190ME12	HAN	1280x1024	250cd/m²	450:1	70/60 70/70	376.32x301.056	30,000	T	
19.0	HT190E01-100	HYD	1280x1024	300cd/m²	700:1	75/75 75/60				
19.0	HT190E01	HYD	1280x1024	300cd/m²	700:1	80/80 80/80				
19.0	LB190E01	LG	1280x1024	1000cd/m²	900:1	85/85 85/85	376.32x301.06			
19.0	LM190E01-C4	LG	1280x1024	250cd/m²	400:1	88/88 88/88	376.3x301.1	40,000	T	
19.0	LM190E02-A4	LG	1280x1024	250cd/m²	500:1	88/88 88/88	376.3x301.1	40,000	T	
19.0	LM190E3-B4K1	LG	1280x1024	250cd/m²	500:1	70/70 70/70	376.3x301.1	50,000	T	
19.0	LM190E03	LG	1280x1024	250cd/m²	500:1	70/70 65/75	376.32x301.056	50,000		
19.0	LM190E03-B4	LG	1280x1024	250cd/m²	500:1	70/70 65/75	376.32x301.056	50,000		
19.0	LM190E04	LG	1280x1024	250cd/m²	500:1	70/70 65/75				
19.0	LM190E02-B4	LG	1280x1024	270cd/m²	500:1	88/88 88/88				
19.0	LM190E05	LG	1280x1024	280cd/m²	600:1	89/89 89/89	376.3x301.1	50,000	T	
19.0	LM190E06	LG	1280x1024	300cd/m²	800:1	80/80 80/80	376.3x301.1			
19.0	LM190E08	LG	1280x1024	300cd/m²	800:1	75/85 85/85	376.32x301.056			
19.0	LM190E05	LG	1280x1024	250cd/m²	700:1	89/89 89/89	376.3x301.1			
19.0	NL128102BC29-10	NEC	1280x1024	300cd/m²	450:1	88/88 88/88	376.32x301.056	CCFL		
19.0	NL128102BM29-05A	NEC	1280x1024	1000cd/m²	900:1	85/85 85/85	376.32x301.056			MONO
19.0	LTM190EP01	SAM	1280x1024	300cd/m²	1500:1	89/89 89/89				
19.0	LTM190ET01	SAM	1280x1024	250cd/m²	1000:1	80/80 80/80				
19.0	LTB190E2	SAM	1280x1024	250cd/m²	1500:1	90/90 90/90	376.3x301.1			
19.0	LTM190E1-L01/L03	SAM	1280x1024	250cd/m²	500:1	85/85 85/85	376.3x301.1	50,000	T	
19.0	LTM190E4	SAM	1280x1024	250cd/m²	1500:1	90/90 90/90	376.3x301.1			
19.0	LTM190E1	SAM	1280x1024	250cd/m²	500:1	85/85 85/85				
19.0	LTM190EX	SAM	1280x1024	300cd/m²	1000:1	80/80 80/80	376.3x301.1			
19.0	LTM190EX-L01	SAM	1280x1024	300cd/m²	700:1	75/75 75/60				
19.0	LQ190E1LX31	SHA	1280x1024	450cd/m²	400:1	85/85 85/85				
19.0	LQ190E1LW01	SHA	1280x1024	300cd/m²	700:1		376.32x301.056			
19.0	LQ190E1LW41	SHA	1280x1024	450cd/m²	900:1		376.32x301.056			
19.0	LTA190W1	SAM	1280x768	450cd/m²	800:1	85/85 85/85	412.8x247.7	50,000	T	W
19.0	LTA190W1-L03	SAM	1280x768	450cd/m²	800:1	85/85 85/85				
19.0	LTA190W1-L01	SAM	1280x768	450cd/m²	800:1	85/85 85/85				
19.0	M190PW01 V5	AUO	1440x900	300cd/m²	1000:1	85/85 80/80	408.24x255.15	2xCCFL		
19.0	M190PW01V0	AUO	1440x900	300cd/m²	700:1	90/90 90/90				
19.0	M190A1	CMO	1440x900	300cd/m²	500:1	80/80 80/80				

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
19.0	V190C1	CMO	1440x900	400cd/m ²	500:1	75/60 80/80				
19.0	M190A1-L02	CMO	1440x900	300cd/m ²	850:1	80/80 85/85	410.4x256.5			
19.0	M190A1-L07	CMO	1440x900	400cd/m ²	1000:1	80/80 85/85	410.4x256.5			
19.0	LM190WX1	LG	1440x900	300cd/m ²	1000:1	80/80 85/85	408.24x255.15			
19.0	LTM190BT03	SAM	1440x900	300cd/m ²	1000:1	80/80 80/80				
19.0	LTM190M2-L31	SAM	1440x900	300cd/m ²	1000:1	80/80 80/80				
19.0	LTM190M2	SAM	1440x900	300cd/m ²	700:1	75/60 75/75				
19.0	LTM190EX	SAM							T	
19.6	F8961	CMO	1600x1200	1140cd/m ²	600:1	85/85 85/85	398.4x298.8			Medical
19.6	IAUX61	ID	1600x1200	1140cd/m ²	600:1	85/85 85/85	398.4x298.8	30,000	T	
19.6	IAUX61F	ID	1600x1200	500cd/m ²	600:1	85/85 85/85				
19.7	LQ197V3DZ89	SHA	640x480	450cd/m ²	600:1	85/85 85/85				
19.7	LQ197V3DZ31	SHA	640x480	450cd/m ²	500:1	85/85 85/85				
20.0	T200XW02	AUO	1366x768	450cd/m ²	700:1	70/70 80/80				
20.0	T200XW01	AUO	1366x768	450cd/m ²	800:1	85/85 85/85				
20.0	M200RW01 V0	AUO	1600x900	250cd/m ²	1000:1	85/85 80/80	442.8x249.1	2xCCFL		
20.0	CLAA200UA02	CPT	1600x900	250cd/m ²	1000:1					
20.0	CLAA200UA03	CPT	1600x900	250cd/m ²	1000:1					
20.0	LM200WD1	LG	1600x900	300cd/m ²	1000:1	80/80 85/85	442.8x249.1			
20.0	LM200WD3	LG	1600x900	250cd/m ²	1000:1	80/80 85/85	442.8x249.1			
20.0	LM200WD2	LG	1600x900	250cd/m ²	1000:1	89/89 89/89	442.8x249.1			
20.0	CLAA201VA07	CPT	640x480	400cd/m ²	1200:1					
20.0	LTA200V1-L01	SAM	640x480	500cd/m ²	600:1	85/85 85/85	406.1x304.6	50,000	T	W
20.1	HT20X21	HYD	1024x768	500cd/m ²	550:1	90/90 90/90				
20.1	NL128102AC31-02	NEC	1280x1024	250cd/m ²	300:1	85/85 85/85				
20.1	V201B1	CMO	1366x768	500cd/m ²	1000:1	88/88 88/88	444.633x249.984			
20.1	LC200XW1	LG	1366x768	500cd/m ²	700:1	90/90 90/90				
20.1	M201P1-L03	CMO	1400x1050	300cd/m ²	1000:1	80/80 85/85	408.24x306.18			Fast Response
20.1	M201P1-L01	CMO	1400x1050	300cd/m ²	700:1	80/80 80/80				
20.1	M201UN03 V0	AUO	1600x1200	250cd/m ²	1000:1	89/89 89/89	408x306			
20.1	M201UN04 V0	AUO	1600x1200	300cd/m ²	800:1	80/80 80/80	408x306			
20.1	M201UN02	AUO	1600x1200	250cd/m ²	600:1	85/85 85/85	408x306	50,000	T	
20.1	M201UN02 V2	AUO	1600x1200	250cd/m ²	700:1	85/85 85/85				
20.1	M201UN02 V6	AUO	1600x1200	300cd/m ²	1000:1	89/89 89/89				
20.1	LM201U04-A3	LG	1600x1200	250cd/m ²	400:1	88/88 88/88	408.0x306.0	30,000	T	
20.1	LM201U02-A3M1	LG	1600x1200	250cd/m ²	350:1	80/80 80/80				
20.1	LM201U03-A3	LG	1600x1200	250cd/m ²	350:1	88/88 88/88				
20.1	LM201U04	LG	1600x1200	250cd/m ²	500:1	89/89 89/89				
20.1	LM201U05	LG	1600x1200	300cd/m ²	800:1	89/89 89/89				
20.1	LTM201UX	SAM	1600x1200	300cd/m ²	800:1	80/80 80/80				
20.1	LTM201U1	SAM	1600x1200	300cd/m ²	900:1	90/90 90/90	408.8x306.0			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
20.1	LQ201U1LW11Z	SHA	1600x1200	700cd/m²	1000:1	85/85 85/85	408x306			
20.1	LQ201U1LW21	SHA	1600x1200	250cd/m²	500:1	88/88 88/88	408x306			
20.1	M201EW01 V3	AUO	1680x1050	300cd/m²	1000:1	89/89 89/89	433.4x270.9			
20.1	M201EW02 V0	AUO	1680x1050	300cd/m²	800:1	80/80 80/80	433.4x270.9			
20.1	M201EW02 V8	AUO	1680x1050	300cd/m²	800:1	80/80 80/80	433.4x270.9			
20.1	M201EW02 V8	AUO	1680x1050	300cd/m²	1000:1	85/85 80/80	433.4x270.9			
20.1	M201EW01 VC	AUO	1680x1050	300cd/m²	800:1	85/85 85/85				
20.1	M201EW01 V0	AUO	1680x1050	300cd/m²	800:1	85/85 85/85				
20.1	M201EW01 V1	AUO	1680x1050	450cd/m²	800:1	89/89 89/89				
20.1	B201SW01	AUO	1680x1050	300cd/m²	1000:1	80/80 80/80	433.4x270.9			
20.1	CLAA201WA04	CPT	1680x1050	300cd/m²	1000:1					
20.1	CLAA201WA04A	CPT	1680x1050	300cd/m²	1000:1					
20.1	LM201W01	LG	1680x1050	250cd/m²	600:1	89/89 89/89				
20.1	LM201WE3	LG	1680x1050	300cd/m²	1000:1	80/80 80/80	433.4x270.9			
20.1	LP201WE1	LG	1680x1050	320cd/m²	1000:1	80/80 70/70	433.4x270.9			
20.1	LM201WE2	LG	1680x1050	470cd/m²	1600:1	89/89 89/89				
20.1	LTM201M2	SAM	1680x1050	300cd/m²	1000:1	80/80 80/80				
20.1	NL256204AM15-03A	NEC	2560x2048	850cd/m²	600:1	88/88 88/88	399.36x319.488			Inverter Built in
20.1	NL256204AM15-02	NEC	2560x2048	220cd/m²	450:1	85/85 85/85				
20.1	NL256204AM15-01	NEC	2560x2048	850cd/m²	600:1	85/85 85/85				MONO, Inv. built in
20.1	NL256204AM15-01A	NEC	2560x2048	850cd/m²	600:1	85/85 85/85				MONO, Inv. built in
20.1	T201VN02V0	AUO	640x480	500cd/m²	600:1	85/85 85/85				
20.1	V201V2	CMO	640x480	500cd/m²	1000:1	85/85 85/85	408x306			
20.1	V201V1	CMO	640x480	500cd/m²	600:1	70/70 80/80	408x306			
20.1	V201V1-T02	CMO	640x480	450cd/m²	500:1	70/70 80/80	408x306	60,000	T	
20.1	HSD201TV11-A	HAN	640x480	500cd/m²	600:1	88/88 88/88				
20.1	HT201V01	HYD	640x480	450cd/m²	700:1	75/75 70/60				
20.1	LC201V02-A3	LG	640x480	450cd/m²	400:1	85/85 85/85	408.0x306.0	50,000	T	
20.1	LC201V02	LG	640x480	550cd/m²	500:1	89/89 89/89				
20.1	NL6448AC63-01	NEC	640x480	500cd/m²	400:1	65/65 50/50				
20.1	A201SN02	AUO	800x600	450cd/m²	700:1	70/70 60/60				
20.1	A201SN02 V5	AUO	800x600	450cd/m²	700:1	80/80 60/60				
20.1	A201SN02 V4	AUO	800x600	450cd/m²	500:1	80/80 60/60				
20.1	A201SN01	AUO	800x600	500cd/m²	500:1	80/80 80/80	408x306	50,000	T	
20.6	HV260WX1	HYD	1366x768	550cd/m²	800:1	90/90 90/90				
20.8	F8921	CMO	2048x1536	1000cd/m²	900:1	85/85 85/85	423.9x318			Medical
20.8	F8920	CMO	2048x1536	400cd/m²	400:1	85/85 85/85	423.9x318			Medical
20.8	HV208QX	HYD	2048x1536	400cd/m²	700:1	89/89 89/89				
20.8	HV208QX1	HYD	2048x1536	800cd/m²	800:1	89/89 89/89				
20.8	ITQX20E	ID	2048x1536	235cd/m²	300:1	85/85 85/85	423.9x318.0	30,000	T	
20.8	ITQX21	ID	2048x1536	800cd/m²	600:1	85/85 85/85	423.9x318.0	30,000	T	

TFT Übersicht

Size	Model	Supplier	Resolution	Brighness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
20.8	ITQX21H	ID	2048x1536	800cd/m²	600:1	85/85 85/85				
20.8	ITQX21G	ID	2048x1536	800cd/m²	600:1	85/85 85/85				
20.8	ITQX20H	ID	2048x1536	800cd/m²	600:1	85/85 85/85				
21.0	LTM210M2-L01	SAM	1680x1050	300cd/m²	900:1	89/89 89/89	453.6x283.5	10,000	T	
21.0	LTM210M2	SAM	1680x1050	300cd/m²	1000:1	90/90 90/90				
21.3	TX54D11VC0CAC	HIT	1600x1200	250cd/m²	550:1	85/85 85/85				
21.3	NL160120AC27-22B	NEC	1600x1200	860cd/m²	1050:1	88/88 88/88	432.0x324.0	16xCCFL		Inverter built in
21.3	NL160120AC27-20	NEC	1600x1200	950cd/m²	800:1	85/85 85/85	432.0x324.0	50,000		Inverter built in
21.3	NL160120BC27-14	NEC	1600x1200	250cd/m²	550:1	85/85 85/85	432.0x324.0	50,000		
21.3	NL160120BC27-10	NEC	1600x1200	250cd/m²	430:1	85/85 85/85	432.0x324.0			LED Backlight
21.3	NL160120AM27-13A	NEC	1600x1200	1650cd/m²	850:1	85/85 85/85	432.0x324.0			Inverter built in
21.3	NL160120BM27-03	NEC	1600x1200	1000cd/m²	700:1	85/85 85/85	432.0x324.0			MONO
21.3	NL160120BM27-03A	NEC	1600x1200	1000cd/m²	700:1	85/85 85/85	432.0x324.0			MONO
21.3	NL160120AM27-06	NEC	1600x1200	1800cd/m²	600:1	85/85 85/85				
21.3	NL16120AC27-01A	NEC	1600x1200	200cd/m²	250:1	85/85 85/85				
21.3	NL160120BC27-02	NEC	1600x1200	250cd/m²	450:1	85/85 85/85				
21.3	LTM213U4-L01	SAM	1600x1200	250cd/m²	500:1	85/85 85/85	432.0x324.0	50,000	T	
21.3	LTM213U8	SAM	1600x1200	300cd/m²	1000:1	90/90 90/90				
21.3	LTM213U6	SAM	1600x1200	300cd/m²	1000:1	90/90 90/90	432.0x324.0			
21.3	LTM213U6-L01	SAM	1600x1200	300cd/m²	900:1	89/89 89/89				
21.3	NL204153AC21-09	NEC	2048x1536	800cd/m²	750:1	85/85 85/85	433.15x324.86	50,000		Inverter built in
21.3	NL204153AM21-07A	NEC	2048x1536	1450cd/m²	900:1	85/85 85/85	433.2x324.9	50,000		MONO, Inv. built in
21.3	NL204153BC21-02	NEC	2048x1536	235cd/m²	450:1	85/85 85/85	433.2x324.9	50,000		
21.3	NL204153BM21-02	NEC	2048x1536	235cd/m²	450:1	85/85 85/85				
21.3	NL204153BM21-01A	NEC	2048x1536	800cd/m²	700:1	85/85 85/85	433.2x324.9	50,000		MONO
21.3	NL204153BM21-01	NEC	2048x1536	800cd/m²	700:1	85/85 85/85	433.2x324.9	50,000		MONO
21.3	F8980	CMO	2560x2048	750cd/m²	600:1	85/85 85/85	422.4x337.92			Medical
21.3	IAQS80F	ID	2560x2048	750cd/m²	600:1	85/85 85/85				
21.3	IAQS80	ID	2560x2400	750cd/m²	600:1	75/75 75/75	422.4x337.92	30,000	T	
21.5	M215HW01 V0	AUO	1920x1080	300cd/m²	1000:1	85/85 80/80	476.6x268.1	4xCCFL		
21.5	CLAA215FA04	CPT	1920x1080	250cd/m²	1000:1					
21.5	CLAA215FA03S	CPT	1920x1080	250cd/m²	1000:1					
21.5	CLAA215FA01	CPT	1920x1080	300cd/m²	1000:1					
21.5	LM215WF1	LG	1920x1080	300cd/m²	1000:1	80/80 85/85	476.64x268.11			
21.5	LM215WF4	LG	1920x1080	250cd/m²	1000:1	80/80 85/85	476.64x268.11			
21.5	LM215WF2	LG	1920x1080	250cd/m²	1000:1	89/89 89/89	475.2x267.3			
21.6	T216XW01	AUO	1366x768	350cd/m²	2500:1	89/89 89/89	477.4x268.4			
21.6	CLAA216WA01	CPT	1366x768	350cd/m²	1000:1					
21.6	V216C1	CMO	1440x900	400cd/m²	1000:1	88/88 88/88				
22.0	LTA220W1-L01	SAM	1280x720	450cd/m²	500:1	85/85 85/85	487.7x274.3	50,000	T	W
22.0	G220SW01 V0	AUO	1680x1050	300cd/m²	1000:1	89/89 89/89	473.76x296.1	6xCCFL		

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
22.0	M220EW01 V1	AUO	1680x1050	250cd/m²	1000:1	85/85 85/85	473.76x296.1			
22.0	M220EW01 V5	AUO	1680x1050	300cd/m²	1000:1	85/85 85/85	473.6x296.1			
22.0	M220EW01 V0	AUO	1680x1050	300cd/m²	1000:1	80/80 85/85				
22.0	M220Z1-L05	CMO	1680x1050	250cd/m²	1000:1	80/80 85/85	473.76x296.1			High Color Gamut
22.0	M220Z1-L03	CMO	1680x1050	300cd/m²	700:1	80/80 85/85	473.76x296.1			Fast Response
22.0	CLAA220WA01	CPT	1680x1050	300cd/m²	1000:1					
22.0	CLAA220WA09	CPT	1680x1050	300cd/m²	1000:1					
22.0	CLAA220WA09O	CPT	1680x1050	300cd/m²	1000:1					
22.0	LM220WE5	LG	1680x1050	250cd/m²	1000:1	80/80 85/85	473.76x296.1			
22.0	LM220WE3	LG	1680x1050	300cd/m²	1000:1	80/80 80/80	473.8x296.1			
22.0	LM220WE1	LG	1680x1050	300cd/m²	1000:1	80/80 80/80	473.8x296.1			
22.0	LTM220M1-L01	SAM	1680x1050	300cd/m²	1000:1	80/80 80/80				
22.0	LTM220M1	SAM	1680x1050	280cd/m²	1000:1	80/80 80/80				
22.5	NL192120AC25-02	NEC	1920x1200	420cd/m²	800:1	88/88 88/88	483.84x302.4	12xCCFL		
23.0	V230W1	CMO	1280x720	500cd/m²	800:1	88/88 88/88	510.72x312.8			
23.0	HSD230WX12-A	HAN	1280x768	500cd/m²	500:1	88/88 88/88				
23.0	HSD230WX01-A	HAN	1280x768	500cd/m²	350:1	85/85 85/85				
23.0	LC230W01-A2	LG	1280x768	450cd/m²	400:1	85/85 85/85	501.1x300.7	50,000	T	W
23.0	LC230W01	LG	1280x768	550cd/m²	500:1	89/89 89/89				
23.0	T230XW01	AUO	1366x768	450cd/m²	700:1	80/80 80/80	508.152x285.696			
23.0	HSD230WX12-B	HAN	1366x768	500cd/m²	500:1	88/88 88/88				
23.0	HSD230TW14-A	HAN	1366x768	600cd/m²	600:1	88/88 88/88				
23.0	LC230WX3	LG	1366x768	450cd/m²	800:1	90/90 90/90				
23.0	LC230W02-A5	LG	1366x768	500cd/m²	550:1	88/88 88/88	508.2x285.7	50,000	T	W
23.0	LC230W02	LG	1366x768	600cd/m²	550:1	89/89 89/89				
23.0	LTA230W2	SAM	1366x768	450cd/m²	1200:1	85/85 85/85				
23.0	LTA230W1-L02	SAM	1366x768	500cd/m²	800:1	89/89 89/89				
23.0	LM230WF4	LG	1920x1080	400cd/m²	1000:1	80/80 85/85	509.184x286.416			
23.0	LM230WF5	LG	1920x1080	250cd/m²	1000:1	80/80 85/85	509.184x286.416			
23.0	LM230WF2	LG	1920x1080	300cd/m²	1000:1	89/89 89/89	509.184x286.416			
23.0	LM230WF1	LG	1920x1080	300cd/m²	1000:1	80/80 85/85	509.184x286.416			
23.0	M230UW01 V0	AUO	1920x1200	200cd/m²	700:1	85/85 85/85				
23.0	M230UW01 V1	AUO	1920x1200	250cd/m²	800:1	85/85 85/85				
23.0	LM230W02-A2	LG	1920x1200	235cd/m²	400:1	88/88 88/88	495.3x309.6	50,000	T	W
23.0	LM230WU3	LG	1920x1200	400cd/m²	800:1	89/89 89/89	495.36x309.6			
23.1	LQ231U1LW31	SHA	1600x1200	500cd/m²	600:1	85/85 85/85	470.4x352.8			W
23.1	LQ231U1LW01	SHA	1600x1200	250cd/m²	500:1	85/85 85/85	470.4x352.8			W
24.0	M240HW01 V2	AUO	1920x1080	300cd/m²	1000:1	85/85 80/80	531.8x229.2	4xCCFL		
24.0	M240UW01 V0	AUO	1920x1200	500cd/m²	1000:1	89/89 89/89				
24.0	M240UW01 V2	AUO	1920x1200	300cd/m²	1000:1	89/89 89/89	518.4x324.0			
24.0	M240UW01 V4	AUO	1920x1200	400cd/m²	1000:1	89/89 89/89	518.4x324.0			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
24.0	M240UW01 V1	AUO	1920x1200	450cd/m²	1000:1	80/80 80/80	518.4x324.0			
24.0	M240J1	CMO	1920x1200	500cd/m²	1000:1	85/85 85/85	518.4x324.0			
24.0	LM240WU3	LG	1920x1200	400cd/m²	1000:1	80/80 80/80	518.4x324.0			
24.0	LM240WU4	LG	1920x1200	400cd/m²	1000:1	89/89 89/89	518.4x324.0			
24.0	LM240WU1	LG	1920x1200	500cd/m²	1600:1	89/89 89/89	518.4x324.0			
24.0	LTM240CS01	SAM	1920x1200	400cd/m²	1000:1	89/89 89/89	518.4x324.0			
24.0	LTM240CS06	SAM	1920x1200	400cd/m²	1000:1	89/89 89/89				
24.0	LTM240W1-L01	SAM	1920x1200	220cd/m²	400:1	80/80 80/80	518.4x324.0	50,000	T	W
24.0	LTA240W1-L01	SAM	1920x1200	220cd/m²	400:1	80/80 80/80	518.4x324.0	50,000	T	W
24.0	LTM240W1-L04	SAM	1920x1200	300cd/m²	1000:1	89/89 89/89				
24.0	LTM240M2	SAM	1920x1200	500cd/m²	1000:1	90/90 90/90				
24.0	LTM240M1	SAM	1920x1200	500cd/m²	1000:1	89/89 89/89				
25.0	LM250WF1	LG	1920x1080	300cd/m²	1000:1	80/80 85/85	552.96x311.04			
25.5	LQ255T3LZ19	SHA	1366x768	500cd/m²	800:1	85/85 85/85				
26.0	260XW01 V5	AUO	1280x768	500cd/m²	600:1	85/85 85/85				
26.0	T260XW02 V5	AUO	1280x768	500cd/m²	600:1	85/85 85/85				
26.0	T260XW01 V3	AUO	1280x768	550cd/m²	600:1	85/85 85/85				
26.0	T260XW01	AUO	1280x768	600cd/m²	600:1	85/85 85/85	566.4x339.8	50,000	T	W
26.0	LC260W01-A5K1	LG	1280x768	450cd/m²	500:1	88/88 88/88	566.4x339.8	50,000	T	W
26.0	LC260W01	LG	1280x768	600cd/m²	600:1	88/88 88/88				
26.0	T260XW02	AUO	1366x768	450cd/m²	3000:1	89/89 89/89	575.8x323.7			
26.0	V260B1	CMO	1366x768	500cd/m²	800:1	80/80 80/80	575.77x323.71			
26.0	CLAA260WA05	CPT	1366x768	450cd/m²	3000:1					
26.0	HSD260WX11-A	HAN	1366x768	550cd/m²	550:1	88/88 88/88				
26.0	HV260XW01	HYD	1366x768	500cd/m²	800:1	89/89 89/89				
26.0	LC260WX2	LG	1366x768	600cd/m²	4000:1	89/89 89/89	575.77x323.71			
26.0	LC260W02	LG	1366x768	600cd/m²	1200:1	89/89 89/89				
26.0	LTA260AP02	SAM	1366x768	450cd/m²	4000:1	89/89 89/89				
26.0	LTA260W2-L01	SAM	1366x768	500cd/m²	1000:1	85/85 85/85	575.55x232.7	10,000	T	W
26.0	LTA260	SAM	1366x768	450cd/m²	2000:1	85/85 85/85	575.8x323.7			
26.0	LTA260W2	SAM	1366x768	500cd/m²	1200:1	85/85 85/85				
26.0	M260J1	CMO	1920x1200	500cd/m²	1000:1	85/85 85/85	550.08x343.8			LCS&DCR
26.0	CLAA260WU09	CPT	1920x1200	400cd/m²	1000:1					
26.0	CLAA260WU01	CPT	1920x1200	400cd/m²	1000:1					
26.0	CLAA260WU03	CPT	1920x1200	400cd/m²	1000:1					
26.0	LM260WU2	LG	1920x1200	400cd/m²	1000:1	89/89 89/89	550.08x343.8			
26.0	LM260WU1	LG	1920x1200	500cd/m²	1600:1	89/89 89/89	550.08x343.8			
27.0	V270W1-L01	CMO	1280x720	450cd/m²	500:1	85/85 85/85	597.12x335.88	50,000	T	
27.0	V270B1	CMO	1366x768	550cd/m²	1000:1	88/88 88/88	596.3x335.2			
27.0	M270HW01 V0	AUO	1920x1080	400cd/m²	1000:1	85/85 80/80	597.6x336.15	4xCCFL		
27.0	LM270WF1	LG	1920x1080	400cd/m²	1000:1	80/80 85/85	597.89x336.31			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
27.0	LTM270M1	SAM	1920x1200	500cd/m²	1000:1	90/90 90/90				
28.1	LQ281L1LW14	SHA	2048x2048	225cd/m²	450:1	85/85 85/85	503.8x503.8			
28.3	LQ283G1TW11	SHA	2560x2048	225cd/m²	400:1	85/85 85/85	560.64x448.51	15xCCFL		
29.0	V296W1-L01	CMO	1280x768	450cd/m²	500:1	85/85 85/85	643.2x385.92	50,000	T	
29.6	T296WX01	AUO	1280x768	600cd/m²	600:1	85/85 85/85	643.2x385.9	50,000	T	W
30.0	LC300W01-C5	LG	1280x768	450cd/m²	350:1	85/85 85/85	643.2x391.8	50,000	T	W
30.0	LC300W01-A5	LG	1280x768	450cd/m²	350:1	85/85 85/86	643.2x385.9	50,000	T	W
30.0	LC300W01-A3	LG	1280x768	450cd/m²	350:1	85/85 85/85				
30.0	M300F1	CMO	2560x1600	300cd/m²	1000:1	88/88 88/88	641.28x400.8			High Color Gamut
30.0	LM300W01-A3	LG	2560x1600	280cd/m²	400:1	88/88 88/88	677.3x436.8	50,000	T	
30.0	LTM300M1	LG	2560x1600	280cd/m²	1000:1	88/88 88/88				
30.0	LM300WQ3	LG	2560x1600	300cd/m²	1000:1	89/89 89/89	641.28x400.8			
30.0	LM300WQ5	LG	2560x1600	370cd/m²	3000:1	89/89 89/89	641.28x400.8			
30.0	LM300WQ1	LG	2560x1600	300cd/m²	1000:1	90/90 90/90				
30.0	LTM300M1	SAM	2560x1600	400cd/m²	1000:1	90/90 90/90				
31.5	T315XW01	AUO	1366x768	500cd/m²	1200:1	88/88 88/88				
31.5	T315XW01 V0	AUO	1366x768	550cd/m²	800:1	85/85 85/85	697.7x392.3	60,000	T	
31.5	T315XW01	AUO	1366x768	500cd/m²	800:1	85/85 85/85				
31.5	T315XW02	AUO	1366x768	450cd/m²	3000:1	89/89 89/89	697.7x392.3			
31.5	T315XW02 V1	AUO	1366x768	500cd/m²	1200:1	89/89 89/89				
31.5	T315XW01 V5	AUO	1366x768	500cd/m²	800:1	85/85 85/85				
31.5	V315B1	CMO	1366x768	500cd/m²	1500:1	88/88 88/88	697.68x392.25			
31.5	CLAA315WA01	CPT	1366x768	450cd/m²	3000:1					
31.5	LQ315T3LZ28	SHA	1366x768	500cd/m²	800:1	85/85 85/85				
31.5	LQ315T3LZ49	SHA	1366x768	500cd/m²	1200:1	88/88 88/88	697.69x392.26	16xCCFL		
31.5	T315HW02	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	698.4x392.8			
31.5	T315HW02 VX	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	698.4x392.8			
32.0	LTA320W1-L02	SAM	1280x720	450cd/m²	500:1	85/85 85/85	745.6x464.6	50,000	T	W
32.0	LTA320W1-L01	SAM	1280x768	450cd/m²	500:1	85/85 85/85	745.6x464.6	50,000	T	W
32.0	V320B1-L01	CMO	1366x768	550cd/m²	800:1	85/85 85/85	708.9x398.6	60,000	T	
32.0	V320B1	CMO	1366x768	550cd/m²	1000:1	88/88 88/88	708.95x398.59			
32.0	CLAA320WF01SC	CPT	1366x768	500cd/m²	1500:1					
32.0	TX80D17VC0CAC	HIT	1366x768	500cd/m²	800:1	89/89 89/89				
32.0	HT320WX1	HYD	1366x768	500cd/m²	800:1	89/89 89/89				
32.0	LC320W1-A4	LG	1366x768	500cd/m²	500:1	88/88 88/88	697.7x392.3	50,000	T	W
32.0	LC320WX5	LG	1366x768	500cd/m²	5000:1	89/89 89/89	697.68x392.25			
32.0	LC320W01	LG	1366x768	500cd/m²	5000:1	89/89 89/89	697.68x392.25			
32.0	LTi320AA02	SAM	1366x768	450cd/m²	3500:1	89/89 89/89				
32.0	LTi320WT-L07-0	SAM	1366x768	600cd/m²	1500:1	89/89 89/89	697.68x392.25			
32.0	LTA320	SAM	1366x768	500cd/m²	3000:1	89/89 89/89	697.7x392.3			
32.0	LTA320AB02	SAM	1366x768	450cd/m²	5000:1	89/89 89/89				

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
32.0	LTA320W2	SAM	1366x768	450cd/m²	1000:1	89/89 89/89				
32.0	LTA320W1-L03	SAM	1366x768	500cd/m²	1000:1	89/89 89/89	697.7x392.3	10,000	T	W
32.0	LTA320WT	SAM	1366x768	500cd/m²	1200:1	90/90 90/90				
32.0	LTA320W2-L03	SAM	1366x768	500cd/m²	1000:1	85/85 85/85				
37.0	T370XW02	AUO	1366x768	450cd/m²	3000:1	89/89 89/89	819.6x460.8			
37.0	T370XW01 V2	AUO	1366x768	500cd/m²	1000:1	88/88 88/88				
37.0	T370XW01	AUO	1366x768	500cd/m²	1200:1	88/88 88/88	819.6x460.8			
37.0	T370XW01 V1	AUO	1366x768	500cd/m²	1000:1	88/88 88/88				
37.0	CLAA370WF02S	CPT	1366x768	500cd/m²	2000:1					
37.0	LC370W1-A5K1	LG	1366x768	500cd/m²	500:1	88/88 88/88	819.6x460.8	50,000	T	W
37.0	LC370WX4	LG	1366x768	500cd/m²	5000:1	89/89 89/89	819.36x460.89			
37.0	LC370WX1	LG	1366x768	500cd/m²	1600:1	90/90 90/90				
37.0	LC370W01-A5	LG	1366x768	500cd/m²	1200:1	88/88 88/88				
37.0	LQ370T3LZ39	SHA	1366x768	500cd/m²	800:1	85/85 85/85	819.6x460.8	18xCCFL		
37.0	LQ370T3LZ59	SHA	1366x768				819.6x460.8			
37.0	T370HW02	AUO	1920x1080	500cd/m²	3000:1	89/89 89/89	819.36x460.89			
37.0	T370HW02 VX	AUO	1920x1080	500cd/m²	3000:1	89/89 89/89	819.36x460.89			
37.0	T370HW01 V0	AUO	1920x1080	550cd/m²	800:1	85/85 85/85	894.8x460.9	60,000	T	
37.0	T370HW01	AUO	1920x1080	550cd/m²	800:1	85/85 85/85				
37.0	V370H1	CMO	1920x1080	550cd/m²	600:1	88/88 88/88	820.8x461.7			
37.0	LC370WU3	LG	1920x1080	500cd/m²	5000:1	89/89 89/89	819.36x460.89			
37.0	LC370WU2	LG	1920x1080	500cd/m²	5000:1	89/89 89/89	819.36x460.89			
37.0	LC370UW1	LG	1920x1080	600cd/m²	1600:1	90/90 90/90				
40.0	LTA400W01-L01	SAM	1280x760	450cd/m²	600:1	85/85 85/85	871.7x523.0	50,000	T	W
40.0	LTA400W01-L02	SAM	1280x760	450cd/m²	600:1	85/85 85/85	871.7x523.0	50,000	T	W
40.0	LTA400W02-L01(16:9)	SAM	1366x768	500cd/m²	800:1	85/85 85/85	885.2x487.7	50,000	T	W
40.0	LTA400WS	SAM	1366x768	500cd/m²	1200:1	90/90 90/90				
40.0	LT1400WT-L02	SAM	1366x768	700cd/m²	2000:1	89/89 89/89	885.17x497.66			
40.0	LTA400WT	SAM	1366x768	500cd/m²	1200:1	90/90 90/90				
40.0	LT1400WT	SAM	1366x768	700cd/m²	1200:1	89/89 89/89				
40.0	T400HW02	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	885.6x498.1			
40.0	LT1400HA03	SAM	1920x1080	700cd/m²	3000:1	89/89 89/89				
40.0	LT1400HA01	SAM	1920x1080	450cd/m²	4000:1	89/89 89/89				
40.0	LTA400HS-LH1	SAM	1920x1080	450cd/m²	1200:1	88/88 88/88				
40.0	LTA400HS	SAM	1920x1080	500cd/m²	1200:1	90/90 90/90				
40.0	LTA400HS-L01	SAM	1920x1080	500cd/m²	1200:1	88/88 88/88				
42.0	T420XW01	AUO	1366x768	500cd/m²	1200:1	89/89 89/89				
42.0	G420XW01 V0	AUO	1366x768	700cd/m²	2000:1	89/89 89/89	930.3x523.0			
42.0	G420XW02 V0	AUO	1366x768	500cd/m²	2500:1	89/89 89/89	930.3x523.0			
42.0	G420XW02 V2	AUO	1366x768	500cd/m²	1500:1	89/89 89/89	930.3x523.0			
42.0	LC420WX7	LG	1366x768	500cd/m²	5000:1	89/89 89/89	930.25x523.01			

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
42.0	LC420WX7-SLE1	LG	1366x768	500cd/m²	5000:1	89/89 89/89	930.25x523.01			
42.0	LC420W02-AK	LG	1366x768	500cd/m²	400:1	88/88 88/88	930.25x523.01	50,000	T	W
42.0	LC420W02	LG	1366x768	500cd/m²	1600:1	90/90 90/90				
42.0	LC420W02-A6	LG	1366x768	500cd/m²	500:1	89/89 89/89				
42.0	LTA420W1-L01	SAM	1366x768	450cd/m²	800:1	85/85 85/85	930x523	50,000	T	W
42.0	T420HW01	AUO	1920x1080	500cd/m²	1500:1	89/89 89/89	930.24x523.36			
42.0	T420HW04 VX	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	930.24x523.26			
42.0	T420HW04	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	930.24x523.26			
42.0	P420HW01 V0	AUO	1920x1080	700cd/m²	3500:1	89/89 89/89	930.24x523.26			
42.0	T420HW01 V3	AUO	1920x1080	500cd/m²	2000:1	89/89 89/89	930.25x523.26			
42.0	V420H1	CMO	1920x1080	600cd/m²	1000:1	88/88 88/88	930.24x523.26			
42.0	LC420WU5	LG	1920x1080	500cd/m²	5000:1	89/89 89/89	930.24x523.26			
42.0	LC420WU4	LG	1920x1080	500cd/m²	5000:1	89/89 89/89	934.24x523.26			
42.0	LC420WU1	LG	1920x1080	650cd/m²	1600:1	90/90 90/90				
46.0	LTA460WS-L03	SAM	1366x768	500cd/m²	1000:1	89/89 89/89	1018x572.5	10,000	T	
46.0	LTA460WT	SAM	1366x768	500cd/m²	1200:1	90/90 90/90				
46.0	LTA460WT-LH1	SAM	1366x768	500cd/m²	1200:1	88/88 88/88				
46.0	LTA460WT-L03	SAM	1366x768	500cd/m²	1200:1	89/89 89/89				
46.0	LTA460WS	SAM	1366x768	500cd/m²	1200:1	88/88 88/88				
46.0	LTA460WT	SAM	1366x768	700cd/m²	1200:1	89/89 89/89				
46.0	LT1460AA03	SAM	1366x768	700cd/m²	3000:1	89/89 89/89	1018.35x572.54			
46.0	LT1460AA03	SAM	1366x768	1500cd/m²	3500:1	89/89 89/89	1018.35x572.54			
46.0	LT1460WT-L02	SAM	1366x768	700cd/m²	1500:1	89/89 89/89	1018.35x572.54			
46.0	T460HW03	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	1018.08x572.67			
46.0	T460HW03 VX	AUO	1920x1080	500cd/m²	5000:1	89/89 89/89	1018.08x572.67			
46.0	T460HW02	AUO	1920x1080	500cd/m²	2000:1	89/89 89/89	1018.08x572.67			
46.0	T460HW01	AUO	1920x1080	600cd/m²	800:1	85/85 85/85	1019.5x573.5	50,000	T	W
46.0	T460HW01 V3	AUO	1920x1080	600cd/m²	600:1	85/85 85/85				
46.0	LTA460HS-L02	SAM	1920x1080	450cd/m²	800:1	89/89 89/89	1018x572.5	10,000	T	
46.0	LTA460H2-L02	SAM	1920x1080	450cd/m²	800:1	85/85 85/85				
46.0	LT1460HA03	SAM	1920x1080	700cd/m²	4000:1	89/89 89/89				
46.0	LT1460HA01	SAM	1920x1080	450cd/m²	4000:1	89/89 89/89				
46.0	LTA460HS	SAM	1920x1080	500cd/m²	1200:1	90/90 90/90				
46.0	LTA460HS-LH1	SAM	1920x1080	500cd/m²	1200:1	88/88 88/88				
46.0	LK460D3LA29	SHA	1920x1080	500cd/m²	3000:1	88/88 88/88	1018.08x572.67	18xCCFL	T	
46.0	LK460D3LZ19	SHA	1920x1080	450cd/m²	1800:1	88/88 88/88	1018.08x572.67			
47.0	LC470WX1	LG	1366x768	500cd/m²	5000:1	89/89 89/89	1039.68x584.64			
47.0	V470H1	CMO	1920x1080	600cd/m²	1000:1	88/88 88/88	1042.56x586.44			
47.0	LC470WU4	LG	1920x1080	500cd/m²	5000:1	89/89 89/89	1039.68x584.82			
47.0	LC470WU2	LG	1920x1080	500cd/m²	5000:1	89/89 89/89	1039.68x584.82			
47.0	LC470WU1	LG	1920x1080	650cd/m²	1600:1	90/90 90/90				

TFT Übersicht

Size	Model	Supplier	Resolution	Brightness	Contrast	Viewing Angle (U/D L/R)	Display Area	Lamp Life Time	Display Mode TR=Transflective T=Transmissive	Format / Remark
52.0	P520HW01 V0	AUO	1920x1080	700cd/m ²	4000:1	89/89 89/89	1152x688			
52.0	T520HW01	AUO	1920x1080	500cd/m ²	5000:1	89/89 89/89	1152x648			
52.0	T520HW01 VX	AUO	1920x1080	500cd/m ²	5000:1	89/89 89/89	1152x648			
52.0	V520H1	CMO	1920x1080	500cd/m ²	1500:1	88/88 88/88	1152x648			
52.0	LC520WU2	LG	1920x1080	500cd/m ²	10000:1	89/89 89/89	1152x648			
52.0	LC520WU1	LG	1920x1080	500cd/m ²	5000:1	89/89 89/89	1152x648			
52.0	LT1520HB02	SAM	1920x1080	500cd/m ²	3000:1	89/89 89/89				
52.0	LT1520HB01-001	SAM	1920x1080	700cd/m ²	2000:1	89/89 89/89				
52.0	LT1520HB01	SAM	1920x1080		1700:1	89/89 89/89	1152x648			
52.0	LTA520HT	SAM	1920x1080	500cd/m ²	1500:1	90/90 90/90				
52.0	KL520D3LZ89	SHA	1920x1080	450cd/m ²	1500:1	78/78 78/78	1152x648	24xCCFL		
52.0	LK520D3LZ19	SHA	1920x1080	450cd/m ²	1800:1	88/88 88/88	1152x648			
55.0	LC550W01-A5	LG	1920x1080	500cd/m ²	550:1	88/88 88/88	1264x738.4	50,000	T	
55.0	LC550W01	LG	1920x1080	500cd/m ²	1200:1	90/90 90/90				
56.0	V562D1	CMO	3840x2160	600cd/m ²	1000:1	88/88 88/88	1244.16x699.84			
57.0	LTA570HS	SAM	1920x1080	500cd/m ²	1200:1	90/90 90/90				
57.0	LT1570HH-L01	SAM	1920x1080	600cd/m ²	2000:1	89/89 89/89	1251.36x703.89			
57.0	LT1570HH	SAM	1920x1080	500cd/m ²	1200:1	90/90 90/90				
64.5	LK645D3LZ2U	SHA	1080x1920	450cd/m ²	2000:1	88/88 88/88	1428.48x803.52			portrait
64.5	LK645D3LZ1U	SHA	1080x1920	400cd/m ²	700:1		803.52x1428.48			portrait
64.5	P645HW01 V0	AUO	1920x1080	700cd/m ²	2000:1	89/89 89/89	1428.48x803.52			
64.5	T645HW02	AUO	1920x1080	500cd/m ²	4000:1	89/89 89/89	1428.48x803.52			
64.5	T645HW01	AUO	1920x1080	500cd/m ²	2000:1	89/89 89/89	1428.48x803.52			
64.5	LK645D3LZ29	SHA	1920x1080	450cd/m ²	2000:1	88/88 88/88	1428.48x803.52			
64.5	LK645D3LZ1S	SHA	1920x1080	400cd/m ²	700:1		1428.48x803.52			
70.0	LT1700HD02-LED	SAM	1920x1080	2000cd/m ²	2500:1	89/89 89/89		LED Backlight		LED
70.0	LT1700HD01-001	SAM	1920x1080	600cd/m ²	1500:1	89/89 89/89	1549.44x871.56			
82.0	LK816D3LA19	SHA	1080x1920	1500cd/m ²	1500:1	88/88 88/88	1015.74x1805.76	120xCCFL		
82.0	LT1820HT-L01	SAM	1920x1080	600cd/m ²	2000:1	89/89 89/89	1805.76x1015.74			